

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)December 22, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. D. A. Williamson Well No. 1 in.....
 (Company or Operator) (Unit)
 NE 1/4 NE 1/4 of Sec. 23, T. 21S, R. 37E NMPM., Blinebry Oil & Tubb Gas Pool
 (40-acre Subdivision)
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
 (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 7055' - PBTD 6400'
 7 5/8" csg. at 3180' w/1253 sx. 5 1/2" liner from 2915' to 7055' w/425 sx. 6% gel.
 Blinebry Perfs. 5715-5927' Tubbs Perfs. 6205-6254' Abo Perfs. 7000-7050'.
 Propose to kill well w/oil, install BOP & pull all 2" tubing. Run 2" tubing & set in
 Baker Model "D" at 6185' and squeeze Tubb perfs. 6205-6254' w/75 sx. Trinity Inferno.
 Drill out Model "D" & cement to 6300' and pressure test Tubb Perfs. 6205-6254' w/ 1500
 psi for 30 minutes. Drill out cement & Baker CI BP from 6300-6400' and clean out to 7050'.
 Run cement retainer on 2" tubing to 6900' and squeeze Abo perfs. 7000-7050' w/50 sx. Trinity
 Inferno. Perfs. Drinkard pay from 6464 to 6594' w/1 Jet shot per foot. Reference McCullough
 GR-N dated 9-22-53. Run treating packer on 3 1/2" tubing and set at 6400'. Acidize Drinkard
 perfs. w/500 gals. 15% NE acid. Sand-oil frac. w/30,000 gals. Refined oil + 90,000# of 20-40
 sand. Dual complete Blinebry and Drinkard with combination 2 3/8" & 2 1/16" tubing.

Approved..... December 22, 1964
 Except as follows:

Approved
 OIL CONSERVATION COMMISSION

By.....
 Title.....

Socony Mobil Oil Company, Inc.
 Company & Operator

By.....
 Position..... Group Supervisor
 Send Communications regarding well to:

Name..... Socony Mobil Oil Company, Inc.
 Address..... Box 1800, Hobbs, New Mexico