

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission before the work is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE	X	NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

April 5, 1962
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. D. A. Williamson Well No. 1 in A
(Company or Operator) (Unit)

NE 1/4 NE 1/4 of Sec. 23, T. 21-S, R. 37-E, NMPM, Tubb & Elinebry Pool
(40-acre Subdivision)

Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD: 7055'
 PEID: 7050'
 Csg: 10 3/4" @ 323, 7 5/8" @ 3180, 5 1/2" liner @ 7055' (Top of liner @ 2915)
 Perfs: (Elinebry) 5630-5662, 5672-5682; (Tubb) 6205-6254.

Propose to kill well & pull tbq. If oil will not hold well use inverted emulsion mud. Run DR plug into Model "D" pkr. & dump 20' of sand. Squeeze perfs. 5630-5662 w/cement, drill out & test squeezed perfs. Perforate 5 1/2" liner @ 5715, 5723, 5733, 5762, 5770, 5791, 5797, 5821, 5833, 5890, 5900, 5917 & 5927 w/4 conventional jet shots per ft. (Per McCoullough GR/N log dated 9/22/53). Run 3" tbq. to 2915' w/pkr. & holddown. Frac w/20,000 gals lease crude w/ 1/20 #1 Adomite Mark II and 2# 20/40 Mesh Ottawa sand per gal + 16 rubber ball sealers. 15-20 BPM rate. Drill out remainder of cement. Retrieve DR plugs. Pull 3" tbq and run 2" tbq. and complete.

Approved....., 19.....
Except as follows:

Socony Mobil Oil Company, Inc.
Company or Operator

By.....

Position Senior Clerk
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

Name Socony Mobil Oil Company, Inc.

By.....

Address Box 2406, Hobbs, New Mexico

Title.....