

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE 000

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) <u>Fracture treat</u>	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

March 5, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Gulf Oil Corporation Nancy Stephens Well No. 1 in D
(Company or Operator) (Unit)
NW $\frac{1}{4}$ NW $\frac{1}{4}$ of Sec. 24, T. 21-S, R. 37-E, NMPM, Drinkard Pool
(40-acre Subdivision)
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

SEE ATTACHED SHEET

Approved.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By E. J. Fisher
Title

Gulf Oil Corporation
Company or Operator

By [Signature]
Position Area Supt. of Prod.
Send Communications regarding well to:

Name Gulf Oil Corporation
Address Box 2167, Hobbs, New Mexico

It is proposed to abandon Drinkard Oil and recomplete as Terry Blinbry Oil as follows:

1. Pull rods, pump and tubing.
2. Run bridge plug on electric line and set at 5900'. Cap bridge plug with 10' cement.
3. Perforate 5-1/2" casing from 5675-5705', 5750-5795' and 5815-5845' with 4, 1/2" jet holes per foot.
4. Run 2-7/8" tubing with bridge plug and full bore packer, straddle perforations from 5815-5845', treat with 250 gallons mud acid. Treat with 6000 gallons refined oil with 1# sand per gallon. Straddle perforations from 5750-5795' and 5815-5845', treat with 6000 gallons refined oil with 1# sand per gallon, block with crushed mothballs in lease oil, followed with 6000 gallons refined oil with 1# sand per gallon.
5. Straddle perforations from 5750-5795' and treat with 250 gallons mud acid. Treat with 6000 gallons refined oil with 1# sand per gallon. Straddle perforations from 5675-5705', treat with 250 gallons mud acid. Treat with 6000 gallons refined oil with 1# sand per gallon. Pull 2-7/8" tubing, bridge plug and packer.
6. Run 2-3/8" tubing and return well to production.

[illegible]