

DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

RECEIVED

APR 11 1951

OIL CONSERVATION COMMISSION  
HOBBS-OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

April 16, 1951 - Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the Stanolind Oil and Gas Company S. C. Bilberry Well No. 2 in the

Company or Operator NE/4 of Sec. 6, T. 20-S, R. 39-E, N. M. P. M.,  
House-San Andres Field, Lea County.

The dates of this work were as follows: April 10, 1951

Notice of intention to do the work was ~~(XXXXXX)~~ submitted on Form C-102 on April 9 19 51  
and approval of the proposed plan was ~~(XXXXXX)~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

At 5:00 a.m., April 10, 1951, 36 hours after cementing the 7-5/8" casing in two stages, the pipe was tested above the staging plug with 1,150 psi. This pressure was held for 30 minutes and no bleed-off was observed.

After drilling the staging plug, the pipe was tested again with 1,025 psi for 30 minutes. The pressure remained constant.

The float collar, cement, and shoe in the bottom of the casing were drilled and a third test with 1,000 psi made. There was no drop(over)

Witnessed by T. S. Holden - Stanolind Oil and Gas Co. - Head Rabt.  
Name Company Title

Subscribed and sworn before me this 17th

day of APRIL 1951

Notary Public

My Commission Expires November 16, 1954

My commission expires

I hereby swear or affirm that the information given above is true and correct.

Name Ralph H. Hurdick

Position Field Superintendent

Representing Stanolind Oil and Gas Company  
Company or Operator

Address Box "F"; Hobbs, New Mexico

Remarks:

APPROVED  
Date APR 19 1951

Ray J. Hurdick  
Oil & Gas Inspector

Title

in pressure at the end of 30 minutes.  
The tests were considered satisfactory and completion operations  
have been recommended.