CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

Miscellaneous Reports

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days a specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling tions, results of shooting well, results of test of casing shut off, result of plugging of well, and other important tions, even though the work was witnessed by an agent of the Commission. Reports on minor operations need

signed and sworn to before a notary public. See additional i Indicate nature of rep	ort by checking below.	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWIS ALTERING CASING	SE
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		
March 2, 195	Hobbs, New Mex	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:	Date Pla	ice
Following is a report on the work done and the results obtai	ned under the heading noted above at the	***************************************
Stanolind Oil and Gas Company S. C.	Bilberry Well No. #2	in the
ME/A of Sec. 6	T -20-3 R -39-E	N. M. P. M.,
House-San Andres Field	Lea	County
The dates of this work were as follows: March 1,		-
Notice of intention to do the work was (was not) submitted		
and approval of the proposed plan was (was not) obtained		AG. M
Well was spudded in at l tools are being used to drill	DONE AND RESULTS OBTAINED 11:00 A.M. March 1, 1951. Rotary a 13-3/4" hole in which approximately be run.	
Well was spudded in at l tools are being used to drill 300' of 10-3/4" surface pipe	11:00 A.M. March 1, 1951. Rotary a 13-3/4" hole in which appressionally be run.	netely
Well was spudded in at l tools are being used to drill	11:00 A.M. March 1, 1951. Rotary a 13-3/4" hole in which approximately will be run.	
Well was spudded in at l tooks are being used to drill 300' of 10-3/4" surface pipe	1:00 A.M. March 1, 1951. Rotary a 13-3/4" hole in which approxis will be run. Stanolind Oil & G.s. Co. Hd. Company I hereby swear on affirm that the information true and correct. Name Approximation of the contract of t	Rebt.
Well was spudded in at later tooks are being used to drill 300° of 10-3/4" surface pipe Witnessed by	1:00 A.M. March 1, 1951. Rotary a 13-3/4" hole in which approxis will be run. Stanolind Oil & G.s. Co. Hd. Company I hereby swear or affirm that the informatic is true and correct. Name Position Field Fagineer	Rebt. Title
Well was spudded in at later tooks are being used to drill 300° of 10-3/4" surface pipe Witnessed by	Stanolind Oil & G.s. Co. Hd. Company I hereby swear on affirm that the informatic is true and correct. Name Position Field Engineer Representing Stanolind Oil and G. Company or Operator	Rebt. Title on given above
Well was spudded in at later tooks are being used to drill 300° of 10-3/4" surface pipe Witnessed by Ta Sa Holden Name Subscribed and sworn before me this 19.5/	1:00 A.M. March 1, 1951. Rotary a 13-3/4" hole in which approxis will be run. Stanolind Oil & G.s. Ce. Hd. Company I hereby swear on affirm that the information true and correct. Name Position Field Fagineer Representing Stanolind Oil and G.	Rebt. Title on given above
Well was spudded in at tooks are being used to drill 300° of 10-3/4° surface pipe Witnessed by	Stanolind Oil & G.s. Co. Hd. Company I hereby swear on affirm that the information is true and correct. Name Adverse Stanolind Oil and G. Representing Stanolind Oil and G. Company or Operator Address Box "F" - Hobbs, New Man	Rebt. Title on given above
Well was spudded in at tooks are being used to drill 300° of 10-3/4" surface pipe Witnessed by	Stanolind Oil & G.s. Co. Hd. Company I hereby swear on affirm that the information is true and correct. Name Adverse Stanolind Oil and G. Representing Stanolind Oil and G. Company or Operator Address Box "F" - Hobbs, New Man	Rebt. Title on given above