

Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following instructions in Rules and Regulations of the Commission.

RECEIVED

FEB 28 1951

HOBBS-OFFICE

Hobbs, New Mexico


February 28, 1951

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as Stanolind Oil and Gas Company S. C. Bilberry Well No. 2 in NE/4
Company or Operator Lease

of Sec. 6, T 20-S, R 39-E, N. M., P. M., House-San Field, Lea County.



AREA 640 ACRES

LOCATE WELL CORRECTLY

Rotary tools to a proposed total depth of 4480'

The well is 1980 feet (S.) of the North line and 330 feet
~~XXX~~ (W.) of the East line of Section 6, T-20-S, R-39-E

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is S. C. BilberryAddress Hobbs, New Mexico

If government land the permittee is _____

Address _____

The lessee is Stanolind Oil and Gas CompanyAddress Box 591; Tulsa, Oklahoma

We propose to drill well with drilling equipment as follows: _____

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: On file with the Commission

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Seals Cement
13-3/4"	10-3/4"	40.5#	New	300'	Cemented	
9-7/8"	7-5/8"	24 & 26.4#	New	4325'	Cemented -	(100 sx. neat 1st Stage (300 sx. 8% gel 2nd stage 100 sx. neat

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4353 feet.

Additional information: The 7-5/8" casing will be cemented in 2 stages. In the 1st stage, sufficient cement will be used to fill to the base of the salt section at approx. 2731'. Using a staging collar, cement will be raised

Approved _____, 19____
except as follows:

Sincerely yours,

(over)

Stanolind Oil and Gas Company

Company or Operator

By

Position Field Engineer

Send communications regarding well to

Name Ralph L. HendricksonAddress P. O. Box "F"Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By

Title

Oil & Gas Inspector

to a minimum of 200' above the top of the salt section at approximately 1700'. This will be drilled in strict conformance with stage regulations.