

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New MexicoApril 4, 1950

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,


Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Stanolind Oil and Gas Co. Minnie Lee Hester well No. 1 in SE/4 of SW/4

Company or Operator

Lease

of Sec. 6, T. 20-S, R. 39-E, N. M., P. M., House Field, Lea County.N R-39-E

AREA 640 ACRES

The well is 660 feet (N.) (~~S~~) of the South line and 1980 feet (E.) (~~W~~) of the West line of Section 6

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. \_\_\_\_\_ Assignment No. \_\_\_\_\_

If patented land the owner is Minnie Lee Hester

Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is Stanolind Oil and Gas CompanyAddress Box 591, Tulsa, Oklahoma

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary from surface to approx. 7500', unless commercial quantities of oil and/or gas are encountered at a lesser depth.The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: On file with the Commission.

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17-1/2	13-3/8	36# Armco	New	300'	Cemented	400 sx.
11	8-5/8	28&32#H-40	New	3800'	Cemented	500 sx. 8% Gel
		14 & 15 &				100 sx. neat at
		17 - J-55				600 sx. shoe
7-3/8	5-1/2		New	7500'	Cemented	250 sx.

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 7100 feet.

Additional information: The Salado Salt formation will be adequately protected with cement and all rules and regulations of the Commission will be complied with.

Approved APR 6 1950, 19\_\_\_\_

except as follows: \_\_\_\_\_

Sincerely yours,

Stanolind Oil and Gas Company

Company or Operator

By Ralph L. HendricksonPosition Field Superintendent

Send communications regarding well to:

Name Ralph L. HendricksonAddress Box "F", Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By Roy C. Quirk

Title \_\_\_\_\_