

FORMATION RECORD
NEW MEXICO OIL CONSERVATION COMMISSION

AREA 640 ACRES
LOCATE WELL CORRECTLY

Santa Fe, New Mexico

DUPLICATE

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Shell Petroleum Corporation State "M" (Endura)

Company of Operator

3

NE/4

Address

21-S

Well No.

in

of Sec.

T.

Lease

R. 35-E

N. M. P. M.

Eunice

Field,

Lea

County.

Well is

Section 1, 36, 1

feet west of the East line of

If State land the oil and gas lease is No.

Assignment No.

889

If patented land the owner is

Address

If Government land the permittee is

Address

The Lessee is

Shell Petroleum Corporation

Address

Houston, Texas

Drilling commenced

3-14-

19 37

Drilling was completed

4-27-

19 37

Name of drilling contractor

Oil Well Drilling Co.

Address

Hobbs, N.M.

Elevation above sea level at top of casing

3557

feet.

The information given is to be kept confidential until

Not Confidential

19

OIL SANDS OR ZONES

No. 1, from

3732

to

3857

No. 4, from

to

No. 2, from

to

No. 5, from

to

No. 3, from

to

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from

to

feet.

No. 2, from

to

feet.

No. 3, from

to

feet.

No. 4, from

to

feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
12 1/2	40	8	Nat'l.	164	-			
9 5/8	38	8	Wh'lg.	1260	Float			
7	24	10	Nat'l.	3707	"			

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	12 1/2	164	150	Halliburton	10	4 tons
12 1/2	9 5/8	1260	375	Do.	10	
8 1/2	7	3707	175	Do.	10.5	4 tons

PLUGS AND ADAPTERS

Heaving plug—Material

Length

Depth Set

Adapters—Material

Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from

0

feet to

3857

feet, and from

feet to

feet

Cable tools were used from

feet to

feet, and from

feet to

feet

PRODUCTION

Put to producing

4-27

19 37

The production of the first 20 hours was

286

barrels of fluid of which

100

% was oil;

% emulsion;

% water; and

% sediment.

Gravity, Be

If gas well, cu. ft. per 24 hours

Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Blane Cobb

Driller

Clayton Hough

Driller

Joe Johnson

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

20th

day of

May

19 37

Notary Public.

Name

Place

Date

Position

Representing

Company or Operator

My Commission expires

May 13th 1937

Address

Box 1457

Hobbs

N. Mex.

FORMATION RECORD

DATE: 11/15/2017 11:00 AM