


N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

Grid for locating well. AREA 640 ACRES. LOCATE WELL CORRECTLY.

DUPLICATE

Hobbs, N.M.

Shell Petroleum Corporation  
State-H Company or Operator 3 NE/4 15 Address 21-5  
Lease Well No. 3 in NE/4 of Sec. 15, T. 21-S  
R. 35-E N. M. P. M. Eunice Lea County.  
Well is 1980 feet south of the North line and 1260 feet west of the East line of Section 31  
If State land the oil and gas lease is No. Assignment No.  
If patented land the owner is Address  
If Government land the permittee is Address  
The Lessee is Shell Petroleum Corporation Address Box 2099, Houston, Tex  
Drilling commenced 7-8-38 19 Drilling was completed 8-4-38 19  
Name of drilling contractor Drilg. & Exploration Co., Address Dallas, Texas  
Elevation above sea level at top of casing 3607 feet.  
The information given is to be kept confidential until Not confidential 19

OIL SANDS OR ZONES

No. 1, from 3835 to TD No. 4, from to  
No. 2, from to No. 5, from to  
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.  
No. 1, from to feet.  
No. 2, from to feet.  
No. 3, from to feet.  
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FROM	FILLED FROM	PERFORATED FROM TO	PURPOSE
8-5/8"	28 1/2	8	Nat'l.	1578					
5-1/2"	14 1/2	10	"	3787					
2"	4.8 1/2	10	"	3904					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	5-1/2"	1578	600	Halliburton	10.75	
7 1/2"	5-1/2"	3787	260	"	10.75	

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set  
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3207 feet, and from feet to feet  
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 8-4-38 19  
The production of the first 24 hours was 468 barrels of fluid of which 100 % was oil; % emulsion; % water; and % sediment. Gravity Be. 37.7° API @ 68° Fahr.  
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas  
Rock pressure, lbs. per sq. in.

EMPLOYEES

Bruce Driller Crisman Driller  
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 5 day of August 1938  
Name E. L. Kinney  
Position Dist. Sup't.  
Representing Shell Petroleum Corporation  
Address 1515 E. 1st St., Hobbs, N.M.  
Notary Public  
COMMISSION EXPIRES MAY 15, 1941  
Expires