

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Gypsy Oil Company

Company or Operator

North R. R. Bell

Lease

Well No. 1 in SE SE of Sec. 6 T. 21S

R. 36E, N. M. P. M., Eunice Field, Lea County.

Well is 660 feet south of the North line and 660 feet west of the East line of SE SE

If State land the oil and gas lease is No. B-230 Assignment No.

If patented land the owner is Address

If Government land the permittee is Address

The Lessee is Gypsy Oil Company Address Tulsa, Oklahoma.

Drilling commenced October 9th, 1935 Drilling was completed December 5th, 1935

Name of drilling contractor Warren L. Todd Address Dallas, Texas.

Elevation above sea level at top of casing 3586' feet.

The information given is to be kept confidential until ? 19

OIL SANDS OR ZONES

No. 1, from 3720' to 3895' No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from ? Rotary Hole to feet.

No. 2, from to feet.

No. 2, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10 3/4	40	10	Lap.	318'	?				
7-5/8	26	8	New	2753'	?				
5 1/2 OD	17	10	NEW	3761'	?				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13 3/4	10 3/4	318'	250	Halliburton		
9-7/8	7-5/8	2753'	550	"		
6-3/4	5 1/2	3761'	25	"		

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0' feet to 3895' feet, and from feet to feet

Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing December 5th, 1935

The production of the first 24 hours was 511 barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 11th,

day of December, 1935

H. W. Evans

Notary Public.

My Commission expires March 16, 1936

Tulsa, Oklahoma December 11th, 1935

Name R. R. Bell

Position General Superintendent

Representing Gypsy Oil Company

Company or Operator

Address Tulsa, Oklahoma.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0'	145'		Calechie and Red Rock.
	152	UNDETERMINED	Sand
	325		Sand and Red Rock
	365		Red Bed
	704		Red Bed and shells
	821		Red Bed and Red Rock
	928		Red Rock
	999		Red Bed and Lime
	1075		Red Bed
	1107		Red Bed and lime shells
	1127		Red Bed and lime
	1138		Red Rock
	1170		Gyp and Red Bed
	1185		Red Bed and Anhydrite shells
	1292		Anhydrite
	1355		Anhydrite and Salt
	1483		Anhydrite, Salt and potash
	1548		Anhydrite, streaks of Salt
	1755		Anhydrite and salt
	1890		Salt, potash and Anhydrite shells
	1980		Salt and Anhydrite shells
	2079		Salt
	2156		Salt and Potash
	2229		Salt and Anhydrite
	2461		Salt and Anhydrite
	2600		Salt and Anhydrite
	2668		Anhydrite
	2679		Gyp and Anhydrite
	2761		Anhydrite
	2898		Anhydrite
	2998		Anhydrite
	3024		Anhydrite and sandy lime
	3066		Brown lime
	3842		Lime - Top of Upper San Andreas
	3878		Sandy lime
	3895		Lime.