

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Shell Petroleum Corporation Hobbs, New Mexico
Company or Operator Address
State 0 Well No. 2 in Lot # 12 Sec. 6, T. 21 S
Lease
R. 36 E, N. M. P. M., Eunice Field, Lea County.
Well is 660 feet south of the North line and 6660 feet west of the East line of Lot # 12
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Shell Petroleum Corporation Address Box 2099 Houston, Texas
Drilling commenced 11-26 19 36 Drilling was completed 12-30 19 36
Name of drilling contractor Oil Well Drlg. Co. Address Hobbs, New Mexico
Elevation above sea level at top of casing 3554 feet.
The information given is to be kept confidential until Not confidential 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
12 1/2	40	8	Spang	198				Sur oag
9 5/8	36	8	Smith	1219				Cond string
7	24	10	J & L	3754				Prod string
2 1/2	6.5	10	Pitts	3853				Tubing

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	12 1/2	198	150	Halliburton	10.75	4 Tons
12	9 5/8	1218	375	"	10.	
8 3/4	7	3754	225	"	10.50	

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 3841 feet, and from feet to feet
Cable tools were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing 12-30 36 100 %
The production of the first 24 hours was 1320 barrels of fluid of which 32.6 Baume at 50 Fahr. %
emulsion; % water; and % sediment. Gravity, Be
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

Driller Driller
Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Hobbs, New Mexico
Subscribed and sworn to before me this Place Date
day of , 19 Name District Engineer
Notary Public. Position Shell Petroleum Corporation
Representing Company or Operator
My Commission expires Address Box 1457 Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	110		Sand and caliche
110	120		Red beds
120	150		Sand
150	1800		Red beds w/ hard streaks
1800	1840		Anhydrite
1840	1418		Anhydrite and red shale
1418	2607		Anhydrite and salt
2607	2651		Anhydrite
2651	2770		Anhydrite and lime
2770	2995		Lime and anhydrite
2995	3490		Hard grey lime
3490	3621		Hard brown and grey lime
3621	3754		Soft grey lime w/ hard streaks
3754	3784		Soft white crystalline lime stains, tan w/ oil
3784	3809		Light grey crystalline lime w/ streaks of lime
3809	3854		Porous grey saccharoidal and oolitic lime stained brown w/ oil