

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL ABANDON 30-025-08705
5. Indicate Type of Fee STATE ☒ FEE ☐
6. STATE OIL & GAS CASE NO.
7. Name of the well Eunice Monument South Unit
8. 220
9. Eunice Monument, Grayburg-S.A.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Oil Well ☒ Gas Well ☐ Other	
2. Chevron USA, Inc.	
3. 15 Smith Rd. Midland, Tx 79705	
4. Unit Letter M : 3300 feet from the South line and 600 feet from the West line Section 6 Township 21-S Range 36-E NMPM County Lea	
10. (Show whether DR, RKB, RT, GR, etc.)	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐ OTHER: ☐	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐ CASING TEST AND CEMENT JOB ☐ OTHER: ☐

12. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

1. Notify OCD 24 Hrs Prior to MI & RU
2. RIH w/ws Tag Cidr @ 3820' (Grayburg) Displace hole w/MLF, 9.5# Brine w/25# Gel p/BBL
3. Spot 50sx plug 3775' - 3350' (7" shoe, Top 5" Liner, Queen) WOC Tag.
4. Perf 4 holes @ 2700' sqz 50sx plug 2700' - 2600' (B-Salt) WOC Tag.
5. Perf 4 holes @ 1300' sqz 50sx plug 1300' - 1150' (9 5/8" shoe) T-salt WOC Tag.
6. Perf 4 holes @ 300' sqz 50sx plug 300' - 175' (12 1/2" shoe) WOC Tag.
7. 10 sx surface install dry hole marker

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE PERMITTING OF PLUGGING OPERATIONS FOR THE 1103 TO BE APPROVED.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE D. R. Bledsoe TITLE HES SPECIALIST DATE 7/16/2002

Type or print name G.R. BLED SOE Telephone No. 915 687-7153
(This space for State use)

APPROVED BY _____ TITLE PAUL F. KAUTZ DATE JUL 18 2002
Conditions of approval, if any:

ORIGINAL SIGNED BY
PAUL F. KAUTZ
PETROLEUM ENGINEER

81

PLUGGING & ABANDONMENT WORKSHEET

(3 STRING CSNG)

OPERATOR CHEVRO USA Inc
LEASE NAME Eunice Monument South Unit
WELL # 220

SECT 6 TWN 21-S RNG 36-E
FROM 3300 NSL 600 EWL
TD 4204 FORMATION @ TD
PBTD FORMATION @ PBTD

	SIZE	SET @	TOC	TOC DETERMINED BY
SURFACE	12 1/2	232	SURF	Cice
INTMED 1	9 5/8	1231		
INTMED 2				
PROD	7"	3725	2710	CBL

	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1	5"	3400	4200	3400	Cice
LINER 2					

	CUT & PULL	TOP - BOTTOM
INTMED 1		PERFS
INTMED 2		OPENHOLE
PROD		

*REQUIRED PLUGS DISTRICT

	PLUG	TYPE PLUG	SACKS CEMENT	DEPTH
RUSTLER (ANHYD)	1	7" SHOE		3775
YATES	2	B-SALT	50	2700
QUEEN	3	9 5/8 SHOE	50	1300
GRAYBURG	4	12 1/2 SHOE	50	300
SAN ANDRES	5	SURF	10	10
CAPITAN REEF				
DELAWARE				
BELL CANYON				
CHERRY CANYON				
BRUSHY CANYON				
BONE SPRING				
GLORIETA				
BLINBRY				
TUBB				
DRINKARD				
ABO				
WC				
PENN				
STRAWN				
ATOKA				
MORROW				
MISS				
DEVONIAN				

MLF

12 1/2

@ 232

TOC SURF

MLF

9 5/8

@ 1231

TOC

MLF

7"

@ 3725

TOC 2710

2/18/90 Cice

@ 3850 SQZ

PERFS 3864 -

3945

TD 4204