

N.

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Shell Petroleum Corporation

Hobbs, New Mexico

State **F** Company or Operator **I** Lot **14** Sec **6** 21 S
36 E **Quince** in of **Lea**, T.

R. **Center** N. M. P. M., **lot 14** Field, **Sec 6** County.

Well is **889** feet south of the North line and **889** feet west of the East line of **889**

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is Address

If Government land the permittee is **Shell Petroleum Corporation** Address **Houston, Texas**

The Lessee is **7-31-36** Address **8-30-36**

Drilling commenced **Oil Well Drlg. Company** Drilling was completed **Hobbs, New Mexico**

Name of drilling contractor **3560** Address

Elevation above sea level at top of casing feet.

The information given is to be kept confidential until **Not confidential** 19.

3710

OIL SANDS OR ZONES
3860

No. 1, from to No. 4, from to

No. 2, from to No. 5, from to

No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole

No. 1, from to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
12 1/2	50	8	S H	232	-			WSO
9 5/8	36	8	New	1204	Float			"
7	24	10	"	3708	"			"

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/2	12 1/2	232	150			
12 1/4	9 5/8	1204	375			
8 3/4	7	3708	250			

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set

Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from **0** feet to **3860** feet, and from feet to feet

Cable toops were used from feet to feet, and from feet to feet

PRODUCTION

Put to producing **9-16** **3** 19.

The production of the first 24 hours was **193** barrels of fluid of which % was oil: %

emulsion: % water; and **1,167,000** % sediment. Gravity, Ba

If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in.

E.J. Kemnitz
Paul Cunningham

EMPLOYE Sick Bronscum

Driller Driller

Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this

Hobbs, New Mexico October 21, 1936

day of , 19

Name District Engineer

Position Shell Petroleum Corporation

Representing

Notary Public

My Commission expires

Address Box 1457 Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	180		sand and caliche
180	1184		red beds w/ hard streaks
1184	1350		anhydrite
1350	2508		salt and anhydrite
2508	3437		anhydrite
3437	3710		hard grey lime
3710	3860		hard grey lime w. streaks soft lime
TD 3860			