

ILLEGIBLE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION Repr. (OTHER) Casing Leak	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

October 19, 1954
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **J. F. Janda "C"**

Gulf Oil Corporation

(Company or Operator)

Well No. **2** in **M**
(Unit)

S4 1/4 **S4** 1/4 of Sec. **26**, T. **21-S**, R. **36-E**, NMPM., **Burice** Pool
(40-acre Subdivision) **Lee** County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Found casing leak at 3523' and a tight place at 575'. Propose to scrape casing and repair 5-1/2" casing leak as follows:

1. Pull tubing and packer.
2. Run tubing and casing scrapers.
3. Scrape casing from surface to 3795'.
4. Run wire line magnesium bridge plug and set in base of casing.
5. Run Howco HRC tool and check casing.
6. Run magnesium cement retainer and set at 3475'.
7. Attempt to circulate cement thru leak at 3523' to surface of 5-1/2" - 7-5/8" annulus.
8. Wait on cement.
9. Run bit and check casing to retainer then drill out retainer and cement and pressure test casing with 500# for 30 minutes.
10. If pressure holds, drill out bridge plug and return well to production.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By **L. J. Stanley**
Title.....

Gulf Oil Corporation

(Company or Operator)

By **E. J. Janda**

Position **Area Supt. of Prod.**
Send Communications regarding well to:

Name **Gulf Oil Corporation**

Address **Box 2167, Hobbs, N. M.**