

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER) <u>Fracture treat</u>	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)November 12, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Gulf Oil Corporation W. A. Ramsay "A" Well No. 17 in J (Unit)
(Company or Operator) Lease
NW 1/4 SE 1/4 of Sec. 27, T 21-S, R 36-E NMPM, Emmont Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

In order to increase production it is proposed to perforate, acid and fracture treat as follows

1. Pull rods and pump. Shift upper circulating valve. Pull 2-3/8" tubing.
2. Run 2-7/8" tubing with Baker Model "E" anchor and seal assembly. Run Gamma Ray collar log from 3300-3856'.
3. Perforate 5-1/2" casing from 3757-3776' with 1-11/16" swing jet with 4, 1/2" jet holes per foot. Pump 500 gallons MA acid down tubing, squeeze into formation. Treat formation with 20,000 gallons refined oil with 1# SPG in 4 stages of 5,000 gallons each. Inject 50 rubber balls in oil before each stage.
4. Swab and test. Unlatch anchor and pull 2-7/8" tubing. Run 2-3/8" tubing with GOT circulating valve in close position.

Approved....., 19.....
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....

Gulf Oil Corporation
Company or Operator
By B. F. Jorgensen
Position Area Supt. of Prod.
Send Communications regarding well to:

Name Gulf Oil Corporation
Address Box 2167, Hobbs, New Mexico