

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

MAY 1 1949
RECEIVED
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	x		

May 10, 1949

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Stanolind Oil and Gas Company, J. P. Alexander B Well No. 2 in the _____

Company or Operator

Lease

NW/4 of Sec. 5, T. 21, R. 37, N. M. P. M.,

Wildcat Field, Lea County.

The dates of this work were as follows: April 23-25, 1949

Notice of intention to do the work was (~~max-out~~) submitted on Form C-102 on April 5 19 49
and approval of the proposed plan was (~~max-out~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cement plugs and mud intervals were placed as follows:

Cement Plug	12 lb. mud	Cement Plug	12 lb. mud	Casing Salvaged
10018-9960	9960-9700	4320-4250	4250-3890	187' of 9-5/8"
9750-9700	9700-8050	3890-3800	3800-3651	2290' 7"
8050-7900	7900-7150	3651-3500	3500-1376	1347 5"
7150-7100	7100-6864	1376-1350	1350-15	2900' 5-1/2"
6864-6750	6750-4320	15-Surface		

After plugging a 4" marker extending 5' above ground level, was erected and the location was leveled to conform with surrounding terrain.

Witnessed by T. S. Holden Stanolind Oil & Gas Co. Head Roundabout

Name

Company

Title

Subscribed and sworn before me this _____

I hereby swear or affirm that the information given above is true and correct.

10th day of May 19 49

Name Joseph H. Haddock

Position Field Superintendent

Representing Stanolind Oil and Gas Company
Company or Operator

Notary Public

My commission expires 2-23-50

Address _____

Remarks:

APPROVED

MAY 13 1949

Date

Ray J. Haddock
Name

Title