

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well
2. NAME OF OPERATOR  
Conoco Inc.
3. ADDRESS OF OPERATOR  
P.O. Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FSL & 1980' FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☒
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☐
- (other) ☐

## SUBSEQUENT REPORT OF:

- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

RECEIVED  
FEB 29 1980  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

## 5. LEASE

NM 2512

## 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## 7. UNIT AGREEMENT NAME

NMFU

## 8. FARM OR LEASE NAME

Hawk B-1

## 9. WELL NO.

8

## 10. FIELD OR WILDCAT NAME

Blinebry / Drinkard

## 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 9, T-21S, R-37E

## 12. COUNTY OR PARISH

Lea

## 13. STATE

N.M.

## 14. API NO.

## 15. ELEVATIONS (SHOW DF, KDB, AND WD)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

It is proposed to clean-out & acidize subject well as follows:

MIRU & KILL well. POOH w/ retrievable bridge plug @ 6580'. Clean out well bore to 6758'. Spot 378 gal. 15% HCl-NE from 6736' to 6507'.

Acidize Drinkard zone w/ 5460 gal. 15% HCl-NE. Spot 420 gal. acid from 6042' to 5788'. Acidize Blinebry zone w/ 2688 gal. 15% HCl-NE. Flush & swab well. Place on production.

**RE-SET BP TO SEPARATE BLINEBRY - DRINKARD ZONES**

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Wm. R. Butler, Jr. TITLE Admin. Supervisor DATE 2/28/80

APPROVED BY  
CONDITIONS OF APPROVAL IF ANY:  
4365-5  
NMFU-4  
FILE

APPROVED  
AS AMENDED  
FEB 29 1980  
ACTING DISTRICT ENGINEER

(This space for Federal or State office use)

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

RECEIVED

RECEIVED

MAR 4 1980

CH. COMMUNICATION DIV.

RECEIVED  
MAR 4 1980  
CH. COMMUNICATION DIV.

CH. COMMUNICATION DIV.