

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM-2512
2. NAME OF OPERATOR Continental Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 460 Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FSL and 1980' FWL of Sec 9		8. FARM OR LEASE NAME Hawk B-1
14. PERMIT NO.		9. WELL NO. 6
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3512' df		10. FIELD AND POOL, OR WILDCAT Fusselman
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 9, T-21S, R-37E
		12. COUNTY OR PARISH Lea
		13. STATE N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Set 2 7/8" tubing at 6710'. Spotted 50 sacks class C cement w/2% CaCl₂ from 6710' to 6460'. Top of cement at 6507'. Set packer at 5500'. Pumped 200 sacks class C cement w/3% salt per sack and 1/4% CFR-2. Drilled new hole to 7530'. Set 5" 14 # liner at 7528' w/ hanger set at 6406'. Cemented w/ 115 sacks class C cement. PBD at 7297'. Drilled cement from 7297' - 7485'. Perf 7342' - 44' w/ 4 jsp. Set tbg @ 7305'. Treated perfs w/ 500 gals 28% HCL acid. Completed - 5-30-72

18. I hereby certify that the foregoing is true and correct

SIGNED



Administrative Supervisor

DATE

7-31-72

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

AUG 9 1972

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

USGS (5)

FILE

NMFL(4) *See Instructions on Reverse Side

(Held)
M (Dr.)

RECEIVED

AUG 15 1972

OIL CONSERVATION COMM.
HOBBS, N. M.