

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
CONOCO INC.

3. ADDRESS OF OPERATOR
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☐

RECEIVED

JAN 11 1981
NOTE: Results of multiple completion or zone change on Form 9-330.

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/21/80 MIRR. Recover pkr. CO to 6108'. Set pkr 6400'. Acidize w/ 100 bbls. 15% HCL-NE-FE. Divert w/ 650# 50/50 rock salt & Benzoic flakes. Swab. W/lt w/ RBP to 6396', pkr to 6028'. Acidize Tubbs w/ 150 bbls 15% HCL-NE-FE. Divert w/ 1000# 50/50 rock salt & Benzoic flakes. POOH. Place well on production. Tested 20 BO, 14 BW, 242 MCF on 12/23/80.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butterfield TITLE Administrative Supervisor DATE January 14, 1981

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

USGS 5
NMFU 4
FILE

*See Instructions on Reverse Side

APPROVED FOR RECORD
JAN 14 1981
U.S. GEOLOGICAL SURVEY