NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD



Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper

The N. M. P. M. Bruness Spield, Less Country Country of the East line of Sees, 15, T-21-5, I state and the oil and gas lease in No. — Assignment No. — No. 6, from			Shell Oil	omnany of	Operator			Lease			
Site band the cold and ges leads in No											
STRUET LANGE the off and gas lease is No											
patented tand the owner is Argo 011 Corporation Address. Coverament tand the persistre is. Address. Add										1-L1-U, 4	
The Lance to Shell Oil Company Address Box 1877, Hobbs, Her I became to Lance to Shell Oil Company Address Box 1877, Hobbs, Her I have completed 5-175-51 to 51 me of drilling commenced 4-13 10-51. Design Price of drilling contractor Box 2584 feet and drilling contractor Box 2584 feet and drilling contractor Box 2584 feet and formation given in to be kept conditional until Rob confidential to the kept confidential until Rob confidential											
Shell Cil Company The Lessee is Shell Cil Company The Commenced 4-13 1s. 51. Drilling was completed 5-17-51 19 \$2. Imms of defiling contractor Norma Dride, Co											
Address Ft. Voyth, Texas broates above sea level at top of casing 5001 res. Sectormation above sea level at top of casing 5001 res. Sectormation given is to be kept confidential unit	e Lessee is	She	11 011 Co	mpany		,	Address	Box 1	457, Hod	bs, New H	
PROOF STREET OF	illing commenced	4-13		19 5]	Drilling	was compl	eted	5-17-	51	19 51	
AND							Address	Ft. V	orth, Te	X&S	
OH. SANDS OR ZONES OH. SANDS OR ZONES 10. \$1, from											
D. 1, from 8015 to 8175 No. 4, from 10. 3. 2, from 10. No. 5, from 10. 3. 1, from 10. No. 5, from 10. 3. 1, from 10. No. 6, from 10. 4. 1, from 10. No. 6, from 10. 5. 1, from 10. No. 6,	e information given	is to be kep					WH C LE	<u> </u>	<u> </u>	19	
No. 5, from 10 No. 6,	8015							to			
NO. 6, from 10. IMPORTANT WATER SANDS clude data on rate of water inflow and elevation to which water rose in hole. 1. 1, from 10. 1. 2, from 10. 1. 3, from 10. 1. 4, from 10. 1. 4, from 10. 1. 5, from 10. 1. 5, from 10. 1. 606. 1. 4, from 10. 1. 5, from 10. 1. 606. 1. 4, from 10. 1. 606. 1. 5, from 10. 1. 606. 1.											
DIPORTANT WATER SANIS and data on rate of water inflow and elevation to which water rose in hule. 1. from											
10. 1 from 10. 10. 10. 10. 10. 10. 10. 10. 10. 10.	. 0, 110										
A from 10 feet	clude data on rate	of water inf	low and eleva	tion to v	which water	rose in ho	ole.				
CASING RECORD CASING											
CASING RECORD MUDDING AND CEMENTING RECORD MUDDING AND CEMENTING RECORD CASING WHERE SET OF CHEMICAL RECORD CASING WHERE SET OF CHEMICAL TREATMENT CASING PLUS AND ADAPTERS Length Date Plus TREATMENT CASING PLUS AND ADAPTERS Length DATE TREATMENT CASING PLUS AND ADAPTERS CAS											
SIZE PRINCIPLE SIZE PER POOT PER FIGURE MAKE AMOUNT KIND OF CUT A PILLED PROMETED 3 3/8* 32.44 SR Hayler 210* 5/5* 324 SR Hatical 2895* Baker 1/2* 15.55 175 SR Hetional 2895* Baker 3 3/8* 32.75 SR Hetional 2895* Baker 4 1/4* 13 3/8* 22.2 25.0 Pump A plug 5 R 5/8* 2907 2000 Pump A plug 5 R 6/8* 2905 SR Pump A plug 5 R 779 Pump A plu											
NUMBER STATE PROPERTY PROPERT	4, from		to				reet	•			
SIZE FER NOT PIECE INCH. MARE AMOUNT SHOEL PROM PROM TO 3 3 5 3 2 4 5 5 1 2 5 5 5 1 2 5 5 5 5 5 5 5 5 5		0277	Т Т		,		LILED	DMDEA	IR Amen	blibboom	
NUDDING AND CEMENTING RECORD MUDDING AND CEMENTING RECORD PLOS AND ADAPTERS Length Depth Set BECORD OF EMERGENCE TO BECOMEN TO BE THE TRANSPORT TO BE THE TRANSPOR	SIZE PER FOOT	PER INCH			SHOE	FRO	M			101110319	
MUDDING AND CEMENTING RECORD PLUGS AND ADAPTERS PLUGS AND ADAPTERS PLUGS AND ADAPTERS PLUGS AND ADAPTERS PROCORD OF EMICRICAL TREATMENT MERCORD OF EMICRICAL TREATMENT RECORD OF EMICRICAL TREATMENT RECORD OF DRILL-STEM AND SPECIAL TENTS Soo Reverse Side drill-stem or other special tents or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED datery tools were used from 0 feet to 193 feet, and from feet to feet PRODUCTION ut to producing 5-20 1.9 51 her production of the first 24 hours was. 316 barrels of fluid of which 99.8 was oil; % graw well, cu. ft. per 24 hours. Gallons gaseline per 1,000 cu. ft. of gas. MUDDING AND CEMENTING RECORD MUDDING AND CEMENTING RECOR					Rekes						
MUDDING AND CEMENTING RECORD MUDDING AND ADDRESS PLUGS AND ADAPTERS Length. Depth Set. Bapters—Material Size. RECORD OF MUDDING CHEMICAL TREATMENT MUDDING AND ADAPTERS RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED Other tools were used from feet to fe	-3-1										
PLIGS AND ADAPTERS PLIGS AND ADAPTERS PLIGS AND ADAPTERS PLIGS AND ADAPTERS PROPERTY OF CHEMICAL TREATMENT PROPERTY OF CH		l _			Bung	8191				+	
PLUGS AND ADAPTERS PLUGS AND ADAPTERS Aving plus Material Length Depth Set RECORD OF SIZE CONTROL CHEMICAL TREATMENT PLUGS AND ADAPTERS Aving plus Material Length DEPTH CLEANED OUT RECORD OF SIZE CHEMICAL TREATMENT PROBLEM OF SIZE CHEMICAL TREATMENT RECORD OF DRILL-STEM AND SPECIAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS PROBLEM OF SIZE CHEMICAL TREATMENT RECORD OF DRILL-STEM AND SPECIAL TESTS PROBLEM OF SIZE CHEMICAL TREATMENT RECORD OF DRILL-STEM AND SPECIAL TESTS PROBLEM OF SIZE CHEMICAL TREATMENT RECORD OF DRILL-STEM AND SPECIAL TESTS PROBLEM OF SIZE CHEMICAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS PROBLEM OF SIZE CHEMICAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS											
The content of the co											
METHOD USED 1/4 13 3/8 223 250 Pump & plug			MUDDIN	G AND	CEMENTIN	G RECOR	D				
PLUGS AND ADAPTERS PRICE	ZE OF SIZE OF	ERE SET	NO. SACKS	METH	OD USED	MUD	GRAVIT	Y A	MOUNT OF	MUD USED	
PLUGS AND ADAPTERS PLUGS AND ADAPTERS Length Depth Set Size RECORD OF EMOSPHEAN CHEMICAL TREATMENT RECORD OF EMOSPHEAN CHEMICAL TREATMENT SIZE RECORD OF MAINTENANT OF THE TREATMENT 15% LST 1000 gals, 5-20-5 8015-8193 estilts of shooting or chemical treatment. Treated with 1000 gallons acid. Ren was 3 times, well kicked off and flowed 80 bbls, all in 2 hrs. thru 1° choke, cut how acid water. RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from 0 feet to feet, and from feet to feet to rect, and from feet to feet to production of the first 24 hours was 316 barrels of fluid of which 99,8 % was oil; % mulsion; — % water; and 0,2 % sediment. Gravity, in he production of the first 24 hours was 316 barrels of fluid of which 99,8 % was oil; % mulsion; — % water; and 0,2 % sediment. Gravity, in he production of the first 24 hours was 316 barrels of fluid of which 99,8 % was oil; % mulsion; — % water; and 0,2 % sediment. Gravity, in he production of the first 24 hours was 316 barrels of fluid of which 99,8 % was oil; % Mulsion; — % water; and 0,2 % sediment. Gravity, in he production of the first 24 hours was 316 barrels of fluid of which 99,8 % was oil; % PRODUCTION 19,51 here 1,000 cu. ft. of gas 10 here 1 h				ļ							
PLUGS AND ADAPTERS Applies	* 85/8*	2907									
RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED Otary tools were used from 1 (seet to 193 feet, and from 1 (seet to 198 feet to 198 fe	7/8" 5 1/2"	8015	779	Pamp &	b plag						
RECORD OF SHOCKING CHEMICAL TREATMENT Committee			P	LUGS A	ND ADAPT	ERS					
RECORD OF MINISTERS CHEMICAL TREATMENT 155 LST 1000 gals. 5-20-51 8015-8193 Besults of shooting or chemical treatment Treated with 1000 galiene soid. Ren swab 3 times, well kicked off and flowed 80 bbls. oll in 2 hrs. thru 1° choic, cut 405 acid water. RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from 0 feet to 193 feet, and from feet to 194 feet to 195 feet to 195 feet, and from feet to 195	eaving plug—Mater	iaL		Length			I	Depth Set.			
esults of shooting or chemical treatment. Treated with 1000 galions acid. Ren was 3 times, well kicked off and flowed 80 bbls. oil in 2 hrs. thru 1" choke, cut 40% acid water. RECORD OF DRILL-STEM AND SPECIAL TESTS Graverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto to totary tools were used from 0 feet to 193 feet, and from feet to 194 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 feet to 195 feet, and from feet to 195 fee	lapters—Material _			Size							
esults of shooting or chemical treatment. Treated with 1000 galions acid. Ran swab 3 times, well kicked off and flowed 80 bbls. all in 2 hrs. thru 1° choke, cut 40% acid water. RECORD OF DRILL-STEM AND SPECIAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from 0 feet to 193 feet, and from feet to 194 feet able tools were used from feet to 195 feet, and from feet to 195 feet able tools were used from feet to 195 feet, and from feet to 195 feet able tools were used from feet to 195 feet, and from feet to 195 feet able tools were used from feet to 195 feet, and from feet to 195 feet able tools were used from feet to 195 feet feet, and from feet to 195 feet feet feet feet feet feet feet fee		REC	ORD OF	OOUNG.	CHEM	IICAL TR	EATME	NT			
esults of shooting or chemical treatment. Treated with 1000 gallons acid. Ran swab 3 times, well kicked off and flowed 80 bbls. oil in 2 hrs. thru 1° choke, cut 40% acid water. RECORD OF DRILL-STEM AND SPECIAL TESTS TOOLS USED Otary tools were used from 0 teet to 8193 feet, and from feet to feet able tools were used from feet to feet to feet, and from feet to feet able tools were used from 19_51. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools were used from feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools were used from feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools were used from feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet to feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet. PRODUCTION 19_51. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet. Respecial tests or deviation surveys were made, submit report on separate sheet and attach hereto tools used in feet. Respecial tests or deviation surveys were made, submit report on separate s	Non CHELL-W	UND CHIEF	HCAL USED	QUANT	ITY D	ATE	DEPTH CHATE			DEPTH CLEANED OUT	
esults of shooting or chemical treatment. Treated with 1000 galions acid. Ren awab 3 times, well kicked off and flowed 80 bbls. oil in 2 hrs. thru 1° choke, cut 40% acid water. RECORD OF DRILL-STEM AND SPECIAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from 0 feet to feet, and from feet to feet to feet, and from feet to feet to feet to feet, and from feet to feet to producing 5-20 19-51. The production of the first 24 hours was 316 barrels of fluid of which 99.8 % was oil; % nulsion; % water; and 0.2 % sediment. Gravity, in 42° API The gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas ock pressure, lbs. per sq. in. GOR 915 EMPLOYEES Lee Darhes Driller Roy Lynch Driller Driller Roy Lynch Driller				1000							
record of prill-stem and special tests or deviation surveys were made, submit report on separate sheet and attach hereto to survey tools were used from the feet to feet to feet, and from feet to feet to production of the first 24 hours was 1951 he production of the first 24 hours was 316 barrels of fluid of which 99.8 was oil; asswell, cu. ft. per 24 hours feet to gallons gasoline per 1,000 cu. ft. of gas ock pressure, lbs. per sq. in Gor 915 EMPLOYEES Les Darhan Driller Roy Lynch Driller Driller Driller Driller Driller Driller Driller					/ Smil 8.	7-4V-74	901	7-019<i>5</i>			
RECORD OF DRILL-STEM AND SPECIAL TESTS RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from Ofeet to 193 feet, and from feet to PRODUCTION ut to producing 5-20 1951 he production of the first 24 hours was 316 barrels of fluid of which 99.8 % was oil; mulsion; % water; and O,2 % sediment. Gravity, Gallons gasoline per 1,000 cu. ft. of gas ock pressure, lbs. per sq. in. GOR 915 EMPLOYEES Les Darhes Driller Roy Lynch Driller Driller Driller Driller Driller Driller Driller Driller				<u> </u>							
RECORD OF DRILL-STEM AND SPECIAL TESTS See Reverse Side drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from 0 feet to 193 feet, and from feet to 194 feet to 195 feet to 195 feet, and from 195 feet to	sults of shooting of well kicks	r chemical t	reatment T	rested O bbls	with 100	O gallo	khen	ld. Ra	n swab 3	times,	
drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto TOOLS USED otary tools were used from						- AAA 130			· · · · · · · · · · · · · · · · · · ·		
totary tools were used from 0 feet to 8193 feet, and from feet to feet to feet, and from feet to feet to producing 5-20 feet, and from feet to feet to production of the first 24 hours was 116 barrels of fluid of which 99.8 was oil; mulsion; % water; and 0.2 % sediment. Gravity, from feet to gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas ock pressure, lbs. per sq. in. Gor 915 EMPLOYEES Lee Durham Driller Boy Lynch Driller Driller Driller Boy Lynch Driller			RECORD OF	DRILL-S	STEM AND	SPECIAL	TESTS	See 1	Downwan (2444	
otary tools were used from 0 feet to \$193 feet; and from feet to feet to feet to feet, and from feet to feet to producing 5-20 feet, and from feet to feet to feet, and from feet to feet to feet to producing 5-20 feet to feet, and from feet to feet to feet to feet, and from feet to feet											
PRODUCTION ut to producing 5-20 ,19_51 he production of the first 24 hours was 316 barrels of fluid of which 99.8 % was oil; % mulsion; — % water; and 0.2 % sediment. Gravity, 20 API gas well, cu. ft. per 24 hours	drill-stem or other			тос	OLS USED						
PRODUCTION ut to producing 5-20 ,19-51 he production of the first 24 hours was 316 barrels of fluid of which 99.8 % was oil; % mulsion; — % water; and 0.2 % sediment. Gravity, he here approximately app	drill-stem or other		0 fee	et to	193	feet, and	from		feet to	feet.	
the production of the first 24 hours was		i from	fee	t to		feet, and	from		feet to	feet.	
he production of the first 24 hours was	otary tools were used										
gas well, cu. ft. per 24 hours	otary tools were used	from			1_			•			
Gallons gasoline per 1,000 cu. ft. of gas	otary tools were used the tools were used to producing	from5-20		_			which				
OCK pressure, lbs. per sq. in	otary tools were used able tools were used at to producing the production of the	5-20 e first 24 h	ours was_•_	316				カクザ			
EMPLOYEES Les Derhan , Driller Boy Lynch , Driller E. L. Heath, Sr. , Driller , Driller	otary tools were used able tools were used at to producing the production of the nulsion;	5-20 e first 24 h	ours was	% sec	diment. Gr	avity, 🎥					
Les Durhan , Driller	otary tools were used able tools were used at to producing the production of the nulsion;	5-20 e first 24 h	ours wasand	316 % sec	diment. Gr Gallons	avity, 🌺					
E. L. Heath, Sr. , Driller, Driller,	otary tools were used able tools were used at to producing the production of the nulsion;	5-20 e first 24 h	ours wasand	316 % sec	diment. Gr Gallons GOR	avity, 🌺					
	otary tools were used able tools were used at to producing the production of the nulsion;	5-20 e first 24 h	ours wasand0.2	316 % sec	diment. Gr Gallons GOR PLOYEES	avity, negasoline pe	er 1,000	cu. ft. of	gas		
COMMATION RECORD ON OTHER SIDE	otary tools were used able tools were used at to producing to production of the nulsion; gas well, cu. ft. per ock pressure, lbs. per large park	5-20 e first 24 h% water; 24 hours er sq. in	ours wasand0.2	316 ——% sec ————————————————————————————————————	diment. Gr Gallons GOR PLOYEES er	avity, R gasoline pe 915	er 1,000	cu. ft. of	gas	, Driller	

FROM	то	THICKNESS IN FEET	RMATION RECORD FORMATION
9 5000 7340 7597 7954 8003 8057 8175 8187	5000 7340 7597 7954 8003 8057 8175 8187 8193	5000 2340 257 357 49 54 118 12	No samples: Dolomite w/streaks lime and anhydrite Shale w/streaks sand Sand w/streaks shale & dolomite Sandy dolomite Lime w/streaks dolomite Dolomite Granite wash Granite
TOPS BY	SCHLUMBI BOER:		
HcKee Ellembur Granite	ra,sh	7597 (-4140) 8003 (-4546) 8175 (-4718) 8187 (-4730)	
Granite	-	8187 (-4730)	
	#		
	, .		
		,	
ţ			
	4		