

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILL	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRORATION OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

## Santa Fe, New Mexico

### MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the school on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Roswell, New Mexico  
(Place)

August 5, 1963  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company Argo Well No. 3 in K  
(Company or Operator) (Unit)  
NE 1/4 SW 1/4 of Sec. 15, T. 21S, R. 37E, NMPM, Blinebry/Drinkard Pool  
(40-acre Subdivision)  
Lea County.

### FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

**PROPOSED OPERATION:** Recomplete from Blinebry Gas to Blinebry Oil & Dual w/existing Drinkard.

1. Run GR/N w/CCL from 6390' - 2850'.
2. Set retrievable bridge plug at 5900' or approximately 25' below lowest Blinebry oil perforations (perforations to be selected from GR/N log). Dump sand on bridge plug.
3. Set PERC above 5543' and squeeze cement Blinebry perforations 5543' - 5554', 5565' - 5597', 5604' - 5645', & 5663' - 5693'. Clean out cement to top of sand fill above bridge plug.
4. Perforate selected intervals between 5725' - 5875'.
5. Run frac tubing and FER packer. Set packer between squeeze perforations and new perforations.
6. Treat Blinebry w/1500 gallons 15% NEA using ball sealers. Treat w/20,000 gallons lease crude containing 1# 20-40 mesh sand & 1/20# Mark II Adomite/gallon.
7. Clean out sand and pull retrievable bridge plug, packer and 3" tubing. Run GR Tracer Survey.
8. Run two strings of 2 1/16" production tubing and place both zones on production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....  
Title.....

Shell Oil Company

Company or Operator

By..... R. A. Lowery..... Original Signed By  
R. A. LOWERY

Position..... District Exploitation Engineer  
Send Communications regarding well to:

Name..... Shell Oil Company  
Address..... P. O. Box 1858, Roswell, New Mexico