## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Checking Be	elow	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)  ACIDIZING	<u> </u>
	12-29-52 (Date)	Hobbs, New Maxice.	e)
Following is a report on the work	done and the results obtained under the heading	noted above at the	
(Company or O		(Lease)	
(Contracto	Tadosignated,	in the 1/4 577 1/4 of	Sec. 15
г. <b>21 -S</b> , R <b>37 -E</b> , NMPM.,	Undesignated (Blinebry Gas)Pool,	Lon	County.
The Dates of this work were as follows:	10-9-52		·
Notice of intention to do the work (wa	s) (submitted on Form C-102 on	(Cross out incorrect words)	, 19 <b>52</b>
and approval of the proposed plan (wa		(42.1.2.	
DETA	ILED ACCOUNT OF WORK DONE AND RESU	ULTS OBTAINED	
			n 5543
Acidized throu	gh easing perforations opposite F	Linebry gas section fro	
Acidized throu feet to 5695 f	gh casing perforations opposite E	Linebry gas section fro	
Acidized throu feet to 5695 f	gh easing perforations opposite F	Linebry gas section fro	
Acidized throu feet to 5695 f	gh casing perforations opposite E	Linebry gas section fro	
Acidized throu feet to 5695 f	gh casing perforations opposite E	Linebry gas section fro	
Acidized throu feet to 5695 f	gh casing perforations opposite E	Linebry gas section fro	
Acidized throu feet to 5695 f	gh casing perforations opposite E	Linebry gas section fro	
Acidized throw feet to 5695 f flowed gas @ 6	gh easing perforations opposite E est w/3500 gallons 15% IST acid. estimated rate of 3 MMed/day.	Minebry gas section from	lond,
Acidized throu feet to 5695 f	gh casing perforations opposite E	Minebry gas section from	lond,
Acidized throughout to 5695 f	gh easing perforations opposite E  cet w/3500 gallons 15% IST acid.  stimated rate of 3 MMef/day.  Shell Oil Company)  I hereby certify t	Minebry gas section from After recovering hole in the information given above is true.	lead,
Acidized throw feet to 5695 f flowed gas © 6  Witnessed by	gh easing perforations opposite E  cet w/3500 gallons 15% IST acid.  stimated rate of 3 MMef/day.  Shell Oil Company)  I hereby certify t	After recovering hole  After recovering hole  (Title)  that the information given above is true knowledge.	reman
Acidized throughout to 5695 f	gh easing perforations opposite in the stimuted rate of 3 MMer/day.  Shell Oil Company)  COMMISSION  I hereby certify to the best of my Name	After recovering hole  After recovering hole  (Title)  that the information given above is true knowledge.	reman c and complete