Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained	before	drilling
begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such creturned to the sender. Submit this notice in triplicate. One copy will be returned following approval.	nanges	WIII De
instructions in Rules and Regulations of the Commission.	200	

			New Merico Place		ber 18, 1948	Date	
	VATION CO	mmission,					
anta Fe, Nev entlemen:	w Blexico,						
	are hereby no	otified that it is our	intention to comm	ence the drilling	ng of a well to be l	mown as	
		Incorporated			ell No. 2		
	Company	y or Operator]	Lease		·	
f Sec15	, T 21	-S, R. 37-3	_, N. M., P. M.,	Drinkard	_Field, _Lea	County	
1	N	The well is_	1980 feet (N.) (S.) of the	Morth line an	d 560 fee	
			the East li				
		(Give lo	cation from section	or other lega	l subdivision lines.	Cross out wron	
			the oil and gas leas	se is No119	Assignment	No. 3-9188	
				owner is			
		Address					
		If governmen	nt land the permitt	ee is			
			Shell 011 Co		**		
AREA	MAO ACRES		x 1457 Hobbs,				
LOCATE WE	LL CORRECTL	We propose t	to drill well with dri	lling equipmen	t as follows:		
		wentional rote					
The status of	f a bond for	r this well in confe	ormance with Rule	39 of the G	eneral Rules and H	Regulations of th	
Commission	is as follows:						
We propose	to use the foll	owing strings of cas	ing and to land or	ement them as	indicated:		
Size of	Size of	Weight Per Foot	New or	Depth	Landed or	Backs	
Hole	Casing		Second Hand		Cemented	Cement	
/	13 3/8*	32.4	X	300	cemented	300	
17 1/2"	-2 21."			2050	cemented		
17 1/2" 11"	8 5/8*	327		2950		1500	
17 1/2" 11" 7 7/8"	8 5/8 ¹ 5 1/2 ¹	32 7 15.5 4	N	6540	cemented	900	
7 7/8"	5 1/2" the above plaductive oil or	15.5# an become advisable gas sand should oc		6540	cemented	900	
7 7/8* If changes in the first pro	5 1/2" the above plaductive oil or	an become advisable gas sand should oc	cur at a depth of	6540	cemented	900	
7 7/8* If changes in the first pro Additional in	5 1/2" the above plaductive oil or	an become advisable gas sand should oc	ccur at a depth of	6540 before cementing about 6425 ely yours,	cemented ng or landing casing feet.	900	
7 7/8* If changes in the first pro Additional in	5 1/2" the above plaductive oil or	an become advisable gas sand should oc	ccur at a depth of	6540 before cementing about 6425 ely yours,	cemented	900	
7 7/8* If changes in the first pro Additional in	5 1/2" the above plaductive oil or	an become advisable gas sand should oc	ccur at a depth of	6540 before cementing about 6425 ely yours,	generated and or landing casing feet.	900	
7 7/8* If changes in the first pro Additional in	5 1/2" the above plaductive oil or	an become advisable gas sand should oc	ccur at a depth of 19 Sincer Sh By	before cementing about 6425 ely yours, ell 011 Con	cemented ing or landing casing feet. pany Incorporator Company or Operator	900 . We estimate the	
7 7/8* If changes in the first pro Additional in Approved—except	5 1/2" the above plaductive oil or aformation:	an become advisable gas sand should oc	ccur at a depth of Sincer Sh By Position	6540 before cementing about 6425 ely yours, ell 011 Con	cemented ing or landing casing feet. feet. company or Operator covering Landing Superintende	900 . We estimate the	
7 7/8* If changes in the first pro Additional in	5 1/2* the above plaductive oil or aformation:	an become advisable gas sand should oc	ccur at a depth of Sincer Sh By Position Send of	before cementing about 6425 ely yours, ell 011 Con Frank R. John Districtions	g or landing casing feet. The state of the	we estimate the	
7 7/8* If changes in the first pro Additional in Approved—except	5 1/2" the above plaductive oil or aformation:	an become advisable gas sand should oc	cur at a depth of Sincer Sh By Position Send of	before cementing about 6425 ely yours, ell 011 Con Frank R. John Districtions	g or landing casing feet. The sector of the	we estimate the rated for the corporated	