

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. A-1375
7. Unit Agreement Name
8. Farm or Lease Name Wallace State
9. Well No. 5
10. Field and Pool, or Wildcat Oil Center Blinebry
12. County Lea

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Me-Tex Supply Company
3. Address of Operator P. O. Box 2070 Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER M, 2970 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 21S RANGE 36E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3562' DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	
OTHER Check for casing leak and repair <input checked="" type="checkbox"/>	

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1109.

Test and repair csg. leak between 5-1/2" csg. and 8-5/8" csg.

Pull rods and tbgs. Set Howco RTTS packer at 90' and test above for possible pack-off leak in 8-5/8" x 5-1/2" csg. head. If leak indicated, replace well head packing and re-test. Test csg. for leak. If have leak, pick up Howco RBP plug w/RTTS packer and go in hole w/2-3/8" tbgs. Set RBP plug at 5700', load hole w/water, set packer and test plug. Pressure on csg. to test for leak. If leak indicated, spot 2 sx. 20-40 sand on plug and find leak. Repair leak w/75 sx. Class "C" cement. Drill out and test. If holds okay, retrieve plug and put well back on production.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>W. J. L. Lead</u>	TITLE <u>V.P.</u>	DATE <u>11/2/74</u>
APPROVED BY _____	TITLE _____	DATE _____

RECEIVED

DEC 22 1964

OIL CONSERVATION COMM.
TULSA, N. M.