



COBRA INDUSTRIES, INC.

911 TEXACO RD. - P. O. BOX 2040

HOBBS, NM 88240

(505) 393-1491

Larry Sohaner

Exp. J. D. Kline #9

10-21-36

Shallan-

Blairby mch.
6670

915-688-6722

Howard

COUNTY LEA FIELD Oil Center STATE NM MN 20166
 OPR HUMBLE OIL & REFG. CO. MAP
9 Knox, J. D.
Sec 10, T-21-S, R-36-E CO-ORD
330' FNL, 990' FEL of Sec

Re-Cmp 10-1-70		CLASS <u>OWDF</u> EL <u>3571/2</u>	
CSG & SX - TUBING	FORMATION	DATUM	FORMATION
7 5/8" at 1331' w/450 sx			
4 1/2" at 6220' w/500 sx.			
LOGS EL GR RA IND HC A			

TD 6220'; PBD 6198'
 (Blinebry) Perfs 5875-6059' NO NEW POTENTIAL.

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 6059' TYPE WO

F.R.C. 10-22-70; Opr's Elev. 3571' DF
 PD 6059' WO (Blinebry)
 (Orig. comp 10-26-63 thru Perfs 5875-93',
 OTD 6220', OPB 6198')
 10-19-70 TD 6220'; PBD 6198'; COMPLETE
 Perf 5931-34', 5939-42', 5948-53', 6005-08',
 6013-16', 6020-24', 6053-59' w/1 SPF
 Acid (5875-6059') 3500 gals
 10-22-70 COMPLETION REPORTED

COUNTY	Lea	FIELD	Oil Center-Blinebry	STATE	N.M.	NO.	
OPR.	Humble Oil & Refg. Co.						MAP
NO.	9	LSE	Knox, J. D.				
SEC.	10	T.	21S	BLK.	36E	SUR.	CO-ORD.
LOC. 330' fr N Line & 990' fr E Line of Sec.							
MI.	FROM		CLASS.		EL. 3571'E		
SPUD.	10-4-63	COMP.	10-29-63	FORMATION	DATUM	FORMATION	DATUM
TRT.				LOG:			
				B/Salt 2512			
CSG. & SX.				Queen 3325			
7 5/8"	1331'	450		Gryb 3620			
4 1/2"	6220'	500		SA 3902			
				Glor 5222			
TBG.	DEPTH	SIZE		Bli 5846			
LOGS	EL	GR	RA	IND	HC	A	
				TD 6220'		PB 6196'	
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
5875-93'	Flwd 82 BO + 9 BW 24/64'	1720	38.6	75#	24 hr		
(Blinebry)							
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.	PROP DEPTH			6400'	TYPE		
DATE							

F.R. 9-19-63
 PD 6400' - Blinebry
 10-7-63 Drlg. 2380'.
 10-14-63 Drlg. 5218'.
 Lost circ. @ 4588'.
 10-21-63 TD 6220', laying down drill pipe.
 Cored 5800-5850', rec 50' being:
 12' dolo., w/fair poro., good stain & fluor.,
 18' dolo., w/tr. poro., bldg. oil & stain,
 15' dolo., w/tr. poro. & stain, 5' dolo., NS.
 DST 5770-5850', open 1 hr,
 rec 140' SGCM,
 1 hr ISIP 2062#, FP 69-69#,
 2 hr FSIP 777#.
 Cored 5850-5900', rec 50' being:
 3' dolo., w/good poro., bldg. oil & gas,
 13' dolo., w/poor show, bldg. oil & water,
 34' dolo., w/good poro. & fluor., Bldg. O&G.

10-21-63 -cont.-
Cored 5900-5950', rec 50' being:
21' dolo., w/tr. poro. & fluor., BO&G,
6' dolo., w/tr. fluor., 23' dolo., w/NS.
Cored 5950-5975', rec 25' dolo. & anhy., W/NS.
Cored 6020-6070', rec 50' dolo. & anhy., w/
scatt. tr. Bldg. oil & gas.

10-28-63 TD 6220', PB 6196', WO Potential.
Perf 5875-80', 5891-93' W/1 SPF
Ac. 2000 gals,
swbd dry.
Re-Ac. 5000 gals,
Flwd 66 BNO/16 hrs thru 3/8" chk., TP 75#.