NEW MEXICO	OIL	CONSERV	ATION	CUMM	ISSION

. 4.

	TRIBUTION	
D11	TRIBUTION	
SANTA		1
FILL		
U. 5. G 5.		
LAND OFFICE		
	OIL	
TRANSPORTER	GA5	
PRORATION OFFI	CE	
OPERATOR		

Santa Fe, New Mexico	, 4 - 4	بد ا	1		F.;;	4
----------------------	------------	---------	---	--	------	---

WELL RECORD

•				

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission, Submit in QUINTUPLICATE

If State Land submit 6 Copies

AREA 640 ACRES

	EX SUPPLY COMPANY		Wa]	lace-State	
6	(Company or Operator) Lot	11	3	(Lease) 21.5	36E
Well No.	mton Plincher	XXX of Sec	, T	, R	, NMPM.
OIL OE	micer officers	Pool,	Le a	***************************************	County.
4290 Well is	nter Blinebry South	line	2310	feet from	West
of Section	If State Land the	e Oil and Gas Les	se No. is A-1375	107044406=20 40 50(+08=2024=86000),	
Drilling Commenced	August 9	19.63	Drilling was Completed	≀ugust 28	₁₉ 63
Name of Drilling Cont	Gackle Dri	lling Compa	ny, Inc.		, , , , , , , , , , , , , , , , , , ,
	P.O. Box	1.30 Hobbs	Moss Mossico		
No. 1 (no 5878) <u>.</u> 5		OR ZONES		
No. 1. from. 5878	5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	896	No. 4. from	to	
No. 2 from	5	920	No. 5 from	**	
	to				
No. 3, from	to		No. 0, from	to	***************************************
		IMPORTANT W	ATER SANDS		
Include data on rate o	f water inflow and elevation to	which water rose	in hole.		
No. 1, from	t	o	f	eet	
No. 2, from	t	o	f	cet	
No. 3, from	t	o	f	cet	
No. 4, from	t	o	f	ce t.	
		CASING	RECORD		

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	24	New	1304	Guide	 		Surface
5 1/2 1	5 & 14	New	6032	Guide		5878-96	
						5912-20	Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11	8 5/8	1304	420	P & P		
7 7/8	5 1/2	6035	520	P & P		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

	Acidised	Perfs	ц,С	000	gals	NEA	LST	15	, 2	250	gal	s 2	5%	NEA	LS	T							
		•••••••••		•••••	**********	••••••		••••••	••	••••••	•-•-•		•••••	•••••	•••••	••••••	••••••		•••••	•••••	- <i></i>	••••	
		·····	,	•••••		••••••		•••••													-		
			. #	*		•																	
	Production Stir																						•
		****************																					•
• • • • • • • • • • • • • • • • • • • •		•••••••	•••••			••••••		•••••••							Dept	h Ck	aned	l Out			••	· · · · · · · · · · · · · · · · · · ·	

RECORD OF DRILL-STEM AND SPECIAL \mathcal{P}' (TS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Cable to	o ls were u	sed from	feet to				feet tofeet to	
				OTION				
Put to P	roducing	Sep	tember 4 19 63					
	Ū		during the first 24 hours was		_		98	
OIL WE							juid of which	
					% wate	er; and	% was s	ediment. A.P
	Gr	avity	43					
GAS WE	LL: Th	e production	during the first 24 hours was	•••••••••	M.C.F.	olus	•••••	barrels
	liq	uid Hydroca	rbon. Shut in Pressurelbs.			·		
Length (of Time Si	hut in						
-			LOW FORMATION TOPS (IN CON		CIE WET	W GEOGI	PADUICAI SECTION (TE COM A PROPER
			Southeastern New Mexico	LOBBIAN	CE WAR	II GEOGI	Northwestern New	
T. Anhy	/		T. Devonian	•••••		Т.	Ojo Alamo	
T. Salt			T. Silurian			т.	Kirtland-Fruitland	
		2521 2674	T. Montoya	••••••••••	• • • • • • • • • • • • • • • • • • • •	т.	Farmington	·····
	•	Al.c	T. Simpson				Pictured Cliffs	
	V C.1 3	3360	T. McKee				Menefee	
~ ~	burg	3610	T. Ellenburger T. Gr. Wash				Point Lookout	
	Andres	3922	T. Granite				Dakota	
T. Glori	eta	3268	T. Blinebry	ておてお			Morrison	
			T	••••	••••••	т.	Penn	•••••

			T					
			T			I.		
			FORMATIO	N RECO	RD	1	***************************************	
From	То	Thickness	Formation	From	То	Thickness		···
		in Feet	1 of mation			in Feet	Formation)
0	1249	1249	Red Shale & Sand					
149 115	1415		Anhydrite					
21	2521 2674		Salt Anhydrite & Dolomite					
74	3610		Sand & Dolomite					
10	5268 6 022		Dolomite					
	0022		Sands & Dolomites					
68								,
				ll .		i		
						ł		

I hereby swear or affirm that the information given herewith is a	complete and corre	ect record of the well and	all work done on it so far
as can be determined from available records.	R 9.	penM	9/10/63
Company or Operator. ME-TEX SUPFLY COMPANY	Address P.O.	Box 2070, Hobbs	New Mexico
Name RANDALL F. MONTGOMERY	Posizion ar Title	GEOLOGIST	