

COUNTY	Lea		FIELD	Oil Center-Blaine		STATE	N.M.		NO.	
OPR.	Me-Tex Supply Company						MAP			
NO.	6		LSE	Wallace-State						
SEC.	3	T.	21S	BLK.	36E	SUR.	CO-ORD.			
LOC.	4290' fr S Line & 2310' fr W Line of Sec.									
MI.	FROM		CLASS.		EL 3538					
SPUD	8-9-63		COMP.	9-4-63		FORMATION	DATUM	FORMATION	DATUM	
TRT.	A 4250		LOG.	Anhy	1249					
				Yates	2674					
CSG. & SX.				7-R	2845					
8 5/8"	1304'	680		Queen	3360					
5 1/2"	6035'	600		Gryb	3616					
				SA	3922					
TBG.	DEPTH	SIZE		Glor	5268					
LOGS	EL	GR	RA	IND	HC	A	Bli	5858		
				TD	6035'		PB	6004'		
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.	HRS. TEST		
5878-5920'	Flo. 99	BO + 2 BW	11/64"		43.	1250	400#	24'		
(Blaine)										

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Gackle Drlg. Co. PROP DEPTH 6000' TYPE
DATE

F.R. 8-1-63
PD 6000' - Blaine
Contractor - Gackle Drlg. Co.
8-12-63 TD 1304', WOC.
8-20-63 Drlg. 4080'.
Cored (Grayburg) 3792-3842', rec 50' dolo., w/
scatt. shows.
Cored 3844-94', rec 50' dolo., w/scatt. shows.
8-27-63 TD 5893', stuck DP.
9-4-63 TD 6035', prep to perf.
9-9-63 TD 6035', prep to perf.
9-16-63 TD 6035', PB 6004', COMPLETED.
Perf 5878-96' & 5912-20' W/2 SPF
A W/4250 gals