

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL
	GAS
PRODUCTION OFFICE	
OPERATOR	

WELL RECORD

AREA 640 ACRES
LOCATE WELL CORRECTLY

Gulf Oil Corporation Haskell State
(Company or Operator) (Lease)

Well No. 8, in NE $\frac{1}{4}$ of NE $\frac{1}{4}$, of Sec. 5, T. 21-S, R. 36-E, NMPM.

Undesignated Pool, Lea County.

Well is 600 feet from North line and 500 feet from East line of Section 5, 21-S, 36-E. If State Land the Oil and Gas Lease No. is B-1641-4.

Drilling Commenced 3-11, 19 63. Drilling was Completed 3-27-, 19 63.

Name of Drilling Contractor Moran Drilling Co.

Address Box 1718, Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 3545. The information given is to be kept confidential until _____, 19 _____.

OIL SANDS OR ZONES

No. 1, from 5904 to 5938 No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8"	24	New	1184	Guide			Surface Pipe
4-1/2"	11.6	New	6015	Guide		5904-5938	Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	1195	465	Pump & Plug		
7-7/8"	4-1/2"	6025	597	Pump & Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized with 4000 gallons of 15% HCL acid and fraced treated with 16000 gallons of gelled lease oil containing 1/20# Silica Flour per gallon and 2# SPG

Result of Production Stimulation Pumped 44 BQ. 40 BW in 24 hours

Depth Cleaned Out _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6025 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing May 6, 1963, 19

OIL WELL: The production during the first 24 hours was 84 barrels of liquid of which 52 % was oil; % was emulsion; 48 % water; and % was sediment. A.P.I. Gravity 41.2

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1133	T. Devonian	T. Ojo Alamo	
T. Salt	T. Silurian	T. Kirtland-Fruitland	
B. Salt	T. Montoya	T. Farmington	
T. Yates 2680	T. Simpson	T. Pictured Cliffs	
T. 7 Rivers 2877	T. McKee	T. Menefee	
T. Queen 3300	T. Ellenburger	T. Point Lookout	
T. Grayburg	T. Gr. Wash	T. Mancos	
T. San Andres	T. Granite	T. Dakota	
T. Glorieta 5262	T.	T. Morrison	
T. Drinkard	T.	T. Penn	
T. Tubbs	T.	T.	
T. Abo	T.	T.	
T. Penn	T.	T.	
T. Miss	T.	T.	

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1200		Red Bed & Anhy				
	2824		Anhy & Salt				
	3248		Anhy & Gyp				
	3462		Anhy				
	6025		Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

May 14, 1963 (Date)
Company or Operator Gulf Oil Corporation Address Box 2167, Hobbs, New Mexico
Name Position or Title Area Production Manager