

COUNTY	LEA	FIELD	Oil Center	STATE	NM	MN	20262
OPR	HUMBLE OIL & REFG. CO.						MA /
	1 Blinebry Oil Com #1						
	Sec 10, T-21-S, R-36-E						CO-ORD
	330' FNL, 2310' FWL of Sec						
					CLASS	OWOF	EL 3583' E
	Re-Cmp 10-1-70	FORMATION	DATUM	FORMATION	DATUM		
CSG & SX - TUBING							
7 5/8" at 1347' w/450 sx							
4 1/2" at 6180' w/500 sx.							
LOGS EL GR RA IND HC A							
	TD 6180'; PBD 6158'						
(Blinebry) Perfs 5906-6110' NO NEW POTENTIAL							

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH	6110'	TYPE	WO
DATE				

	F.R.C. 10-22-70; Opr's Elev. 3583' DF
	PD 6110' WO (Blinebry)
	(Orig. comp 9-1-63 thru Perfs 5906-16',
	OTD 6180', OPB 6158')
10-19-70	TD 6180'; PBD 6158'; COMPLETE
	Perf 5970-74', 5986-90', 6000-06', 6012-15',
	6094-98', 6106-10' w/1 SPF
	Acid (5906-6110') 6000 gals
10-22-70	COMPLETION REPORTED

COUNTY	Lea	FIELD	Oil Center-Blinebry	STATE	N.M.	NO.	
OPR.	Humble Oil & Refg. Co.	MAP					
NO.	1	LSE	Blinebry Oil Unit				
SEC.	10	T.	21S	R.	36E	SUR.	CO-ORD
LOC.	330' fr N Line & 2310' fr W Line of Sec.						
MI.		FROM		CLASS.		EL.	3583 5
SPUD.	7-26-63	COMP.	9-2-63	FORMATION	DATUM	FORMATION	DATUM
IRT.	2000 gals acid			LOG:			
				Rust.	1294		
CSG. & SX.				B/Salt	2523		
	7 5/8"	1347'	450	Queen	3350		
	4 1/2"	6180'	500	Gryb	3647		
				SA	3951		
TBG.	DEPTH		SIZE	Glor	5283		
LOGS	EL	GR	RA	IND	HC	A	
				Bli.	5892		
				TD	6180'		
						PB	6158'
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
5906-16'	Flo. 140 BO		10/64"	1039	39.		600#
	(Blinebry)						24'
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.	PROP DEPTH			6400'	TYPE		
DATE							

F.R. 5-23-63, Blinebry. PD 6400'.
 7-29-63 Drlg. 1434' salt & anhy.
 8-5-63 Drlg. 4020' sdy ls.
 8-12-63 Drlg. 4978' ls.
 Lost returns @ 4633'.
 8-19-63 TD 5834', prep to core.
 8-26-63 TD 6180', running casing.
 Cored 5834-42', rec 8' fine xlyn anhy. dolo.,
 BO from PPP.
 Cored 5842-74', rec 32' shly dolo., w/14' having
 tr. to sli. poro. & trace fluor.
 Cored 5874-92', rec 9' shly dolo., w/5' having SSO.
 Cored 5892-5927', rec 35' being: 20' anhy. dolo.,
 w/sli. to fair poro., stain & fluor., 13' anhy.
 dolo., w/tr. fluor., 2' ls., w/NS.
 Cored 6018-68', rec 50' being: 17' shly dolo., w/
 sli. poro. & fluor., 5' dolo., w/tr. poro. & fluor.,
 28' dolo. & anhy., NS.

_____ Humble Oil & Refg. Co., #1 Blinebry Oil Unit - Sec. 10-21S- _____
36E

9-3-63 TD 6180', PB 6158', COMPLETED.
Perf 20 shots 5906-16', treated 2000 gals acid.
