

DISTRIBUTION
DATE
TIME
BY
AND OFFICE
OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

NEW MEXICO
OIL CONSERVATION
COMMISSION
Effective 1-1-80

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	2. Unit Agreement Name
3. Name of Operator Petro-Lewis Corporation	4. Name of Lessee L.G. Warlick
5. Address of Operator P.O. Box 937 Levelland, Texas 79336	6. Well No. 2
7. Location of Well UNIT LETTER <u>B</u> 990 FEET FROM THE North LINE AND 2310 FEET FROM THE E LINE, SECTION 19 TOWNSHIP 21S RANGE 37E N.M.P.M.	8. Field and Pool, or Wizard Blinebry
9. Elevation (Show whether L.F., RT., GR., etc.)	10. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐	REMEDIAL WORK ☒ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOB ☐ OTHER ☐	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐
---	--	--	---

11. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Hot oiled tbq. in Penrose-Skelly and Blinebry zones.
 - Pulled rods out of Penrose-Skelly and Blinebry zones.
 - PCH with 207 joints 2-3/8" tbq. & 2-3/8" x 7" model K packer.
 - RIH with 6-1/8" bit to 6607'. Push packer to 6715'.
 - Acidized Drinkard Perfs (6678-80) with 500 gals. 15% acid. Ran tbq., pump, and rods and pump tested Drinkard with packer set @ 6585'.
 - POH with rods & pump and ran BHP bomb.
 - Set BP @ 6020'. Set packer @ 5670'. Acidized Blinebry perfs (5684-5988) with 1500 gals. 15% NEFE acid. Swabbed and ran BHP bomb.
 - RIH with BP and packer. Set BP @ 3870' and packer @ 3517'. Acidized Penrose-Skelly (3536-3841) with 1500 gals. 15% NEFE acid. Swabbed and ran BHP bomb.
 - POH with BP that was set @ 3870'. Ran 5050' 2-3/8" tbq. with Model K packer and set packer @ 3917'.
 - Stung into Model K packer with 2-3/8" 10rd tbq. for Blinebry vent string.
 - Ran 2-1/16" tbq. for Penrose-Skelly zone.
 - Ran pump and rods in Blinebry zone.
 - Ran pump and rods in Penrose-Skelly zone.
- (see attachment)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael G. Handchen

TITLE Staff Operations Engr.

DATE June 30, 1980

Orig. Signed by

Jerry Sexton

Dist. L. Supv.

APPROVED BY

TITLE

DATE

AND TIONS OF APPROVAL, IF ANY: