

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 15,593 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing Shut In, 19.
OIL WELL: The production during the first 24 hours was barrels of liquid of which % was was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity.
GAS WELL: The production during the first 24 hours was 1.22 M M.C.F. plus 34 barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy	1778'		T. Devonian		T. Ojo Alamo
T. Salt	1910'		T. Silurian		T. Kirtland-Fruitland
B. Salt	3420'		T. Montoya		T. Farmington
T. Yates	3570'		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Delaware Sand	5858'		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres	8785'		T. Granite		T. Dakota
T. G. Dean	11,500'		T.		T. Morrison
T. D. Stream	12,748'		T.		T. Penn
T. T. Atoka	13,003'		T.		T.
T. Morrow	13,508'		T.		T.
T. Lower Mississippian	14,637'		T.		T.
T. Devonian	15,400'		T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	344	344	Caliche				
344	1778	1434	Redbed				
1778	1910	132	Redbed & Anhy & Salt				
1910	2880	970	Anhy & Salt				
2880	3420	540	Anhy & Dolomite				
3420	4872	1452	Anhy, Dolo & Sand				
4872	5782	910	Dolomite				
5782	6140	358	Dolomite & Shale				
6140	7240	1100	Lime & Sand				
7240	8595	1355	Lime				
8595	9370	775	Lime, Sand & Shale				
9370	10558	1188	Lime, Sand, Shale, & Chert				
10558	11088	530	Lime, Sand & Shale				
11088	11786	698	Lime & Shale				
11786	12041	255	Lime, Chert & Shale				
12041	12402	361	Shale				
12402	12890	488	Shale & Chert				
12890	13255	365	Sand, Shale & Chert				
13255	13820	565	Sand & Shale				
13820	14480	660	Sand, Shale & Lime				
14480	14910	430	Sand & Shale				
14910	14950	40	Sand, Lime & Shale				
14950	15053	103	Lime & Chert				
15053	15248	195	Shale & Lime				
15248	15420	172	Shale & Dolomite				
15420	15593	173	Shale, Dolomite & Chert				

Total Depth 15,593' PSTD 14,575' ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

H. D. Raymond June 9, 1964
Address P. O. Box 728 - Hobbs, New Mexico
Position or Title Assistant District Superintendent

Company or Operator TEXACO Inc.
Name H. D. Raymond