

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 031740 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR	9. WELL NO.
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)	10. FIELD AND POOL, OR WILDCAT
At surface 6270' FSL & 660' FEL of Sec. 4, T-21S, R-36E, Lea County, New Mexico, NMPM	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
14. PERMIT NO.	12. COUNTY OR PARISH
15. ELEVATIONS (Show whether DF, RT, GR, etc.)	13. STATE
3545 DF	Lea N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to 5,990' TD on 2-16-65. Ran 188 jts (5,974') of 5 1/2" OD casing and set @ 5,990'. Cemented in two stages W/ stage collar set @ 3601'. 1st stage cemented W/100 sx Class "C" cement 4% gel using 5# tuf plug/sk and 185 sx Class "C" cement 8% gel using 5# tuf plug/sk. 2nd stage cemented W/125 sx Class "C" 8% gel using 1/4# Gelflake/sk. Used 15 centralizers and 30 scratchers. Plug down @ 7:00 p.m. 2-17-65. Top of cement @ 2460' by temperature survey. W.O.C. 24 hrs. Tested casing W/1000# for 30 minutes. Tested O.K.

I hereby certify that the foregoing is true and correct

SIGNED SIGNED ROBERT GAULT III TITLE Staff Supervisor DATE 2-19-65

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

USCS-5, NMOC-2, PAN AM HOBBS-3, ATL-ROS -2, Calif Mid-2

*See Instructions on Reverse Side

J. L. GORDON
ACTING DISTRICT ENGINEER