

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-100
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State XX Fee <input type="checkbox"/>
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		5. State Oil & Gas Lease No. B-230
2. Name of Operator Gulf Oil Corporation		7. Unit Agreement Name
3. Address of Operator Box 670, Hobbs, New Mexico		8. Farm or Lease Name Bell-Ransay (NCT-A)
4. Location of Well UNIT U 940 FEET FROM THE South LINE AND 940 FEET FROM West LINE, SECTION 4 TOWNSHIP 21-S RANGE 36-E NMPM.		9. Well No. 13
15. Elevation (Show whether DF, RT, GR, etc.) 3581 GL		10. Field and Pool, or Wildcat Oil Center Elinebry
		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
 TEMPORARILY ABANDON ☐
 PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
 CHANGE PLANS ☐

REMEDIAL WORK ☐
 COMMENCE DRILLING OPNS. ☐
 CASING TEST AND CEMENT JOB ☒
 OTHER ☐

ALTERING CASING ☐
 PLUG AND ABANDONMENT ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to TD at 6025' March 30, 1965.
 Ran 187 joints and 1 cut joint, 6010' of 4-1/2" 11.60# J-55 ST&C casing set and cemented at 6024', float collar at 5994, DV tool at 3936'. Cemented first stage with 125 sacks of Incoor with 16% gel, 3% salt, .2% R-5 followed by 100 sacks of neat. Circulated 4 hours. Cemented second stage with 225 sacks of Incoor with 16% gel, 3% salt, .2% R-5 followed by 100 sacks of Incoor neat. WOC and W 18-1/2 hours. Drilled cement and DV tool and tested casing with 1600#, 30 min. OK. TB indicated TOC at 2400'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY
 SIGNED C. D. BOWLAND TITLE Area Production Manager DATE April 2, 1965

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY: