

COUNTY	LEA	FIELD	3linebry	STATENM
OPR	GULF OIL CORPORATION			MAP
11 Leonard, Harry (NCT-C)				
Sec. 36, I-1-S, R-26-E				
2200' fr S & W Lines of Sec.				
Spd 2-7-65				
CLASS E				
Cmp 6-17-65				
FORMATION		DATUM	FORMATION	DATUM
LOG				
Gler 5170				
Bli 5693				
Tubb 6267				
LOGS EL GR RA IND HC A				
		TD 6700'	PBD 5930'	

IP Blinebry Perfs 5783-5890' Pmpd 29 BOPD + 5 BLW. Pot. Based on 24 hr test, gravity 35.4, GOR 1724.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. Hillin Drlg. Co.	PROP DEPTH	6700'	TYPE
DATE			

F.R. 1-28-65
FD 6700' - Drinkard
Contractor - Hillin Drlg. Co.

2-15-65 Drlg. 3059'.
2-22-65 ID 5883' dolo., pulling core.
DST (Paddock) 5115-85', open 1 hr 30 mins,
rec 180' DM + 2700' sul wtr, w/NS;
1 hr ISIP 1920#, FP 124-1395#;
1 hr FSIP 1865#.
Cored 5810-35', rec 21' dolo., w/scatt shows.
Cored 5845-83', rec 38' same.

3-1-65 TD 6700', PED 6661', WOC.
Cored 5883-5925', rec 42' dolo., w/scatt shows.

3-8-65 TD 6700', PED 6661', tstg.
Perf (Drinkard) @ 6590' W/5 shots
Ac. 1000 gals.,
swbd dry.
Re-Ac. 1500 gals. 6590'
Swbd dry.

3-15-65 TD 6700', PBD 6661', tstg.
Perf (Drinkard) @ 6514' & 6559' W/5 SPI
Re-Ac. 2000 gals. perf @ 6590'
Ac. 2000 gals. perf @ 6559'
Ac. 2000 gals. perf @ 6514'
Set Ret. BP @ 6604', Pkr @ 6526'
Flwd 239 BLO, 77 BAW + 57 BNO in 16 hrs
thru 43/64" chk., TP 20-100#.

3-22-65 TD 6700', PBD 6661', swbg.
Swbd 38 BO + 36 BW in 8½ hrs 6514-90'
Re-Set Pkr @ 6568'
Swbd 93 BO + 5 BW/6½ hrs.

3-29-65 TD 6700', PBD 6661', tstg on pump.
Pmpd 110 BO + 37 BW/24 hrs.

4-5-65 TD 6700', PBD 6661', tstg on pump.
Pmpd 61 BO + 11 BW/21 hrs.

4-12-65 TD 6700', PBD 6661', tstg.
Swbd dry from perf @ 6590'
Re-Ac. 1000 gals. 6590'
Swbd 10 BAW + 6 BO in 5 hrs & swbd dry.
Re-Ac. 1000 gals. 6514'
Swbd 32 BLO + 10 BAW/6½ hrs.
Re-Ac. 1000 gals. 6559'.
Pmpd 15 BLO, 30 BNO, 19 BAW + 13 BNW/16 hrs.

4-19-65 TD 6700', PBD 6661', tstg on pump.
Pmpd 112 BO + 21 BW/96 hrs.

4-26-65 TD 6700', PBD 6661', pmpg load.
Frac 387 BO + 17,250# sd. 6514-90'
Swbd 156 BLO + 38 BW/11½ hrs.

5-3-65 TD 6700', PBD 6661', tstg on pump.
Pmpd 48 BO, no gauge on wtr in 24 hrs.

5-10-65 TD 6700', PBD 6661', tstg on pump.
 Pmpd 37 BLO, no gauge on wtr in 24 hrs.
5-17-65 TD 6700', PBD 6661', tstg on pump.
 Pmpd 28 BLO, no gauge on wtr in 24 hrs.
5-24-65 TD 6700', PBD 6661', SI.
 Perf (Blinebry) @ 5783', 5828', 5853',
 5890' W/5 SPI
 Set Ret. BP @ 5940'
 Ac. 500 gals.,
 Frac 32,282 gals wtr + 34,520# sd. 5783-5890'
6-1-65 TD 6700', PBD 6661', tstg on pump.
 Pmpd 170 BO + 101 BLW in 120 hrs.
6-7-65 TD 6700', PBD 6661', tstg on pump.
 Pmpd 80 BO + 32 BLW in 72 hrs.
6-14-65 TD 6700', PBD 6661', tstg on pump.
 Pmpd 57 BO + 36 BLW in 72 hrs.

6-21-65 TD 6700', PBD 5930', COMPLETED.
 Drinkard Temporarily Abandoned W/BP @
 5940' & sand to 5930'.
 Did not rec load. (6514-90')
 (-325 BLW from perfs 5783-5890')