

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

AUG 27 11 21 AM '65

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. <b>E-7825</b>

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name <b>None</b>
2. Name of Operator <b>Charles B. Read</b>	8. Farm or Lease Name <b>Sinclair State</b>
3. Address of Operator <b>Box 1822, Roswell, New Mexico</b>	9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>S</b> , <b>2310</b> FEET FROM THE <b>South</b> LINE AND <b>2310</b> FEET FROM THE <b>West</b> LINE, SECTION <b>2</b> TOWNSHIP <b>21S</b> RANGE <b>33E</b> NMPM.	10. Field and Pool, or Wildcat <b>Lynch</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>3797.6' GL</b>	12. County <b>Lea</b>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/14/65: Ran 117 jts. 4 1/2" 9.5# J-55 casing and packer shoe set at 3776' DF.  
Cemented with 100 sx Class C cement, 6% salt, 14.8#/gal. FBTD 3773.50'.  
Tested 1000#, 30 min., no pressure drop, tested o.k. Job completed  
5:15 p.m. WOC 18 hrs.

8/15/65: Pulled and recovered 1850' 8-5/8" intermediate casing which was being used  
for water shut off while drilling with cable tools. Drilled cement plug and  
shoe from 3773' to 3776', bailed out sand and cleaned hole to bottom at  
3783' TD. Released rig at 11:00 p.m. 8/16/65.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Charles B. Read TITLE Operator DATE August 17, 1965

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: