

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name <b>Sarkys</b>	
9. Well No. <b>5</b>	
10. Field and Pool, or Wildcat <b>Wants Abo</b>	
12. County <b>Lee</b>	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator <b>Sinclair Oil &amp; Gas Company</b>	
3. Address of Operator <b>P. O. Box 1920, Hobbs, New Mexico</b>	
4. Location of Well UNIT LETTER <b>0</b> <b>1980</b> FEET FROM THE <b>East</b> LINE AND <b>660</b> FEET FROM THE <b>South</b> LINE, SECTION <b>23</b> TOWNSHIP <b>21S</b> RANGE <b>37E</b> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> <b>Run 5-1/2"OD liner &amp; test</b>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-4-65 Ran 4274' of 5-1/2"OD csg for liner from 3010' to 7284' and cemented w/1050 sks. Encor Class C cement plus 2% Gel slurry Wt. 13.8#. WOC 24 hours.  
6-6-65 Drill cement 2350' to 3010' top of liner w/8-3/4" bit. Tested 8-5/8" csg to 3010' to 1500# for 30 min. Tested Ok. Ran 4-3/4" bit, drill cement inside liner 3010' to 3026' and wash to 7248'. Pressure tested csg 0 to 7248' w/1500# for 30 min. Tested O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *[Signature]* TITLE Superintendent DATE 6-7-65

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

Orig&2cc: OCC Hobbs, cc: Regional Office, cc: file