

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-9659	
7. Unit Agreement Name Grama Ridge Morrow	
8. Farm or Lease Name State GRB Com	
9. Well No. One	
10. Field and Pool, or Wildcat Grama Ridge	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Injection
2. Name of Operator Llano, Inc.
3. Address of Operator P. O. Box 1320, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 34 TOWNSHIP 21-S RANGE 34-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Plugged off tbq and pressured to 1200 psi. Bradenhead sqzd thru 13-3/8 x 9-5/8 annulus w/2000 sx cmt while holding 1200 psi on 9-5/8 x 2-1/2 annulus.
2. Ran temp survey: Top of cement at 600', btm of cement at 8950'.
3. Ran Baker Mod. "F" pkr to 12,680'.
4. Lost seal assembly off btm of tbq. Blanking plug fell out at seal assembly and along side of seal assembly mandrel. Pushed to 12,764' and leave in hole.
5. Ran Baker Lok-Set pkr to 12,636' with "on-off" tool on top.
6. Swbd well in and prepare for injection well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Paul D. Ramey TITLE Vice President DATE 9/11/73

APPROVED BY Joe D. Ramey TITLE Dist. 1, Secy. DATE

CONDITIONS OF APPROVAL, IF ANY: