								L
NO. OF COPIES REC	CEIVED							
DISTRIBUTI	ON	NE	W MEXICO OIL CONSI	ERVATION COMMISS	ION 1	Form C-101		
SANTA FE				HOBB2 0	IFFICE O.C.	evised 1-1-6	÷	
FILE		, ,				5A. Indicate	Type of Lease	
U.S.G.S.				DEC 28	11 28 PH 'S	STATE	FEE	
LAND OFFICE					er an ere e	.e. blute on t	Gan Feare Her	
OPERATOR						E 58	90	
								$\cdot \cdot \cdot \cdot$
ĀF	PLICATION	I FOR PERMIT T	O DRILL, DEEPEN,	OR PLUG BACK		<u> </u>		711
1a. Type of Work						7. Unit Agree		
	DRILL			PLU	ЈО ВАСК 🔲	East W1	<u>lson Deep I</u>	Uni
b. Type of Well						8. Farm or Lo	∋ase Name	
OIL WELL	GAS WELL	OTHER		ZONE	ZONE			
2. Name of Operator	r					9. Well No.	-	
Robert	J. Leo	nard, The					1	
3. Address of Oper	ator					-	d Pool, or Wildcat	
Вох ЦС	)O, Rosw	ell, New M	exico			Wild	sat	
4. Location of Well	UNIT LETTER	K	LOCATED 1980	FEET FROM THE SOUT	th LINE			$\cdot \cdot \cdot \cdot$
- •	0.000	·						M
1847	FEET FROM T	THE Wost	LINE OF SEC. 19	TWP. 21 S RGE.	35 E NMPM	111111	<u> </u>	$\overline{7}\overline{7}\overline{7}$
mmm	uunii					12. County		())
())))))))))))))))))))))))))))))))))))))	////////					Loa		777
	iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii							////
								777
iiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiiii	tttttttt			19. Proposed Depth	19A. Formation	1	20. Rotary or C.T.	
				13,700'	Devoni	<b>A</b> 10	. Date Work will star	
21. Elevations (Sho	w whether DF, 1	RT, etc.) 21A. K	ind & Status Plug. Bond	21B. Drilling Contract	or	22. Approx	. Date Work will star	t
3655 GI		Effe	ative 171/67	To be furnis	shed late	🛨 Jan,	8, 1967	
23.			PROPOSED CASING AI				•	
			FRUPUSED CASING AI	AD CEMENT FROGRAM			<u> </u>	
		SIZE OF CASIN	G WEIGHT PER FOO	T SETTING DEP	TH SACKS OF	CEMENT	EST. TOP	

92-170-170-19

....

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2"	13 3/8"	1.8#	3751	Circulate	
12 1/4"	9 5/8"	10#	55001	620 sks.	
8 5/8"	71	23,26 & 29#	11,500'	450 sks.	
5 7/8"	5" liner			150 sks.	
			13,650'		

If the Mississippian limestone is structurally low, the well will be completed in the Wilson Morrow, otherwise, it will be drilled to the Devonian.

BLOWOUT PREVENTER PROGRAM FOR 8 5/8" AND 5 7/8" HOLES

- 1. Three preventers, 10" 5000 psi WP, two equipped with pipe rams and one equipped with blind rams complete with standard accessories and with two 4" outlets and one 2" outlet
- 2. One Hydril blowout preventer, 10" 5000 psi WP

I hereby certify that the information above is true and complete to the best of my knowledge and belief. Agent for	
Signed Agent 10r Tille Robert J. Leonard	DateDecember 26, 1966
(This space for State Use)	
APPROVED BY TO THE TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	