NO. OF COPIES RECEIVED		Form C-103 Supersedes Old
DISTRIBUTION		Supersedes Old C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION C	COMMISSION Effective 1-1-65
FILE	Hav 2 10	18 M'67 5a. Indicate Type of Lease
U.S.G.S.		
LAND OFFICE		State 📕 Fee
OPERATOR		5. State Oil & Gas Lease No.
· · ·		00-534
(DO NOT USE THIS FOR FOR	DRY NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFEL CATION FOR PERMIT	RENT RESERVOIR.
1. OIL GAS WELL	OTHER. Drilling Well	7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Amerada Petrole	um Corporation	State WE "K"
3. Address of Operator		9. Well No.
P.O. Bear 668 -	Hobbs, New MaxLos	1
4. Location of Well		10. Field and Pool, or Wildcat
7	1980 FEET FROM THE West	1980 Wildcat
UNIT LETTER	15 21_8	
THELINE, SE	CTION TOWNSHIP RANGE _	NMPMN
	15. Elevation (Show whether DF, RT, GR, e	etc.) 12. County
	3615 <sup>1</sup> DF	
	k Appropriate Box To Indicate Nature of No - INTENTION TO:	otice, Report or Other Data SUBSEQUENT REPORT OF:
—		
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WO	
TEMPORARILY ABANDON		RILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS CASING TEST	AND CEMENT JOB
	OTHER	·····
OTHER		
	ļ	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1903.

Finished drilling 6" hele to 12,610' at 2:45 AM 4-24-67.

Ran 35 jts. 5" OD 17.93# N-80 Hydril FJ casing liner set at 12,605<sup>†</sup> with landing collar at 12,486<sup>†</sup>, liner hanger at 11,203<sup>†</sup> and top of tie back sleeve at 11,197<sup>†</sup>. Halliburton commented liner with 130 sx. Class "B" comment with 8/10 of 1% Halad 9 and 10% salt. Pumped plug to 12,486<sup>†</sup> at 11:20 PM 4-25-67 with 3200# PP. Waited 18-1/2 hrs. Drilled comment from 10,925<sup>†</sup> to top of tie back sleeve at 11,197<sup>†</sup>. Tested top of 5" liner and 7" casing with 1500#. Held OK. Ran Baker packer set at 11,142<sup>†</sup>. Tested 7" casing with 2000# and top of 5" liner with 2500#. Held OK. Drilled comment out of top of liner sleeve and liner from 11,197<sup>†</sup> to 11,210<sup>†</sup>. Washed from 11,210<sup>†</sup> to top of plug at 12,486<sup>†</sup>. Tested 7" casing and 5" liner with 2000#. Held OK. Preparing to continue with completion.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

signed B.J. Juny	TITLE District Superintendent	DATE
APPROVED BY		DATE