

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instruction reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0257272

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

JUL 11 11 37 AM '67

2. NAME OF OPERATOR
PHILLIPS PETROLEUM COMPANY

7. UNIT AGREEMENT NAME
Hat Mesa Unit

8. FARM OR LEASE NAME
Hat Mesa

3. ADDRESS OF OPERATOR
Room B-2 Phillips Bldg., Odessa, Texas

9. WELL NO.
1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

10. FIELD AND POOL, OR WILDCAT
Wildcat Devonian

11. SEC., T., R., M., OR BLY. AND
SURVEY OR AREA Section 11,
T-21-S, R-32-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
RKB 3834.4'

12. COUNTY OR PARISH Lea
13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

First intermediate casing ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 13-3/4" hole to 5602'. on June 23, 1967, set 10-3/4" od casing, at 5602', top to bottom, as follows:

69 jts	2889.28'	55.5#	N-80,	ST&C
26 jts	1080.31'	51#	N-80	ST&C
38 jts	1605.57'	55.5#	N-80	ST&C

5575.16'

Cemented with 300 sacks Trinity LW cement w/20%DD and 10% CaCl₂, and 500 sacks regular neat cement. Plug to 5555' with 520 bbls mud.

WOC 6 hours, ran temperature survey, TOC @ 2800', WOC 18 hrs, tested casing and cement with 2000# for 30 minutes, held okay. Started drilling ahead in 9-5/8" hole at 5602'.

18. I hereby certify that the foregoing is true and correct

SIGNED

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

Associate Reservoir Engineer

DATE June 27, 1967

TITLE

DATE

APPROVED
JUL 3 1967
A. R. BROWN
DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.