Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE* (Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [X] GAS WELL [ ] OTHER

5. LEASE DESIGNATION AND SERIAL NO.: NM-2512

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME: NMFU

2. NAME OF OPERATOR: Continental Oil Company

8. FARM OR LEASE NAME: Hawk B-1

3. ADDRESS OF OPERATOR: P. O. Box 460, Hobbs, New Mexico 88240

9. WELL NO.: 19

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface: 1980' FSL & 1980' FEL of Sec. 8, T-21S, R-37E, in Lea County, N. Mex.

10. FIELD AND POOL, OR WILDCAT: Drinkard Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec. 8, T-21S, R-37E

14. PERMIT NO.:

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 3590 DF (est.)

12. COUNTY OR PARISH: Lea

13. STATE: N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:				SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	[ ]	PULL OR ALTER CASING	[ ]	WATER SHUT-OFF	[X]	REPAIRING WELL	[ ]
FRACTURE TREAT	[ ]	MULTIPLE COMPLETE	[ ]	FRACTURE TREATMENT	[ ]	ALTERING CASING	[ ]
SHOOT OR ACIDIZE	[ ]	ABANDON*	[ ]	SHOOTING OR ACIDIZING	[ ]	ABANDONMENT*	[ ]
REPAIR WELL	[ ]	CHANGE PLANS	[ ]				
(Other)				(Other)			

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was spudded at 2:30 P.M. 11-25-68. Drilled 11" hole to 1349' and set 8 5/8" 24# casing at 1322'. Cemented casing with 650 sacks of class C cement with 4% gel - 2% Cal. Cl. Tested casing with 1,000# pressure for 30 minutes, tested OK.

U.S.G.S. - 5 File Pan Am Hobbs 2, Chev. mid 2, Atl. Res. 2

18. I hereby certify that the foregoing is true and correct

SIGNED Robert Gault III TITLE Administrative Section Chief DATE 12-10-68

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
DEC 13 1968
J. L. GORDON
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side