

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
<b>E-1640</b>	
7. Unit Agreement Name	
8. Farm or Lease Name	
<b>State WB "L" Com.</b>	
9. Well No.	
<b>1</b>	
10. Field and Pool, or Wildcat	
<b>Undesignated</b>	
12. County	
<b>Lee</b>	

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <b>Drilling</b>
2. Name of Operator
<b>Amerada Division, Amerada Hess Corporation</b>
3. Address of Operator
<b>P. O. Box 1920, Hobbs, New Mexico</b>
4. Location of Well
UNIT LETTER <b>K</b> <b>1780</b> FEET FROM THE <b>west</b> LINE AND <b>1980</b> FEET FROM THE <b>south</b> LINE, SECTION <b>10</b> TOWNSHIP <b>21-S</b> RANGE <b>35-E</b> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)
<b>3608' DF 3594' GL</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8-3/4" hole to 11,370'. Ran 7" 23# N-80 and 7" 26# C-75, N-80, and P-110 casing. Set at 11,368'. Cemented with 325 sacks lite wate cement with 5# Guilsonite and 1/4# floeal per sack and 180 sacks Class "C" cement with 3/4 of 1% CFR2, 1/4# floeal and 10# salt per sack. Pumped plug to 11,283' at 9:15 p.m. 10-19-69. Waited 46 hrs. Tested 7" csg. with 3000# for 1/2 hr. Held OK. Top cement outside 7" csg. at 7750'. Started drilling 6-1/8" hole at 7 a.m. 10-22-69.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *E. O. Webb* TITLE District Superintendent DATE October 30, 1969

APPROVED BY *John W. Runyon* TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY: