

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3 - NM OCC
1 - File

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Getty Oil Company		8. Farm or Lease Name Percy Hardy
3. Address of Operator Box 249, Hobbs, New Mexico		9. Well No. 4
4. Location of Well UNIT LETTER 0 990 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 17 TOWNSHIP S 21S RANGE 37E NMPM.		10. Field and Pool, or Wildcat Penrose Skelly
15. Elevation (Show whether DF, RT, GR, etc.) 3478 GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 3850'. Ran Dresser Atlas logs. Set 5-1/2" 15.5# J-55 Casing at 3849'. Bottom 428' Ruff-coated, bottom 544' covered w/scratchers and J Ban type Centralizers. Cemented with 750 sacks Halliburton Lite w/15# sack of salt, followed with 150 sacks Class "C" with 3#/sack of salt. Temperature survey indicates good cement at 1300'. WOC 24 hours. Tested 5-1/2" casing with 3700# for 30 minutes, OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	ORIGINAL SIGNED BY EUGENE J. MILLER	TITLE Area Engineer	DATE July 24, 1971
APPROVED BY	TITLE SUPERVISOR DISTRICT		DATE JUL 26 1971
CONDITIONS OF APPROVAL, IF ANY			

RECEIVED

JUL 23 1971

OIL CONSERVATION COMM.
HOBBS, N. M.