

Hanson Oil Corporation  
#2 Kingwood  
Sec. 25, T-21-S, R-36-E  
Lea County, New Mexico

31. Perforated w/1 - 0.40" jet per foot @ 5539', 5545, 5554, 5560, 5574, 5584, 5595, 5603, 5611, 5618, 5638, 5644, 5651, 5665, 5672, 5679, 5686, 5695, 5706, 5711, 5727, 5731, 5744, 5755, 5778, 5783, 5796, 5807, 5819, 5830, 5850, 5872, 5892, 5900, 5916, 5921 & 5928'. 38 holes.

Perforated w/2 - 0.40" jets per foot @ 5206, 5209, 5213, 5214 & 5215'.

| <u>Depth Interval</u> | <u>Amount &amp; kind of material used</u>                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------|
| 5041'                 | 100 sx. Class C cmt squeeze (hole in casing)                                                                 |
| 5206-5215'            | 350 sx. Class C cmt squeeze (Paddock perforations)                                                           |
| 5206-5928'            | Sand-oil fraced w/2500 gals. 15% acid + 112,600 gals. refined frac oil & lease oil + 100,000lbs. 20-40 sand. |
| 5539-5928'            | Sand-water fraced w/2000 gals. 15% acid + 70,000 gals. gelled water + 88,200 lbs. 20-40 sand.                |

**RECEIVED**

**FEB 17 1972**

**OIL CONSERVATION COMM.  
HOBBS, N. M.**