

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-1732

<p align="center"><b>SUNDRY NOTICES AND REPORTS ON WELLS</b></p> <p align="center"><small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small></p>		
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name	
2. Name of Operator Gulf Oil Corporation	8. Farm or Lease Name Harry Leonard (NCT-C)	
3. Address of Operator Box 670, Hobbs, New Mexico 88240	9. Well No. 13	
4. Location of Well UNIT LETTER <u>B</u> <u>510</u> FEET FROM THE <u>Nort h</u> LINE AND <u>1780</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>21-S</u> RANGE <u>36-E</u> NMPM.	10. Field and Pool, or Wildcat Blinebrv	
15. Elevation (Show whether DF, RT, GR, etc.) 3505' GL	12. County Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
-------------------------	-----------------------

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Moran Drilling Company spudded 11" surface hole at 3:00 PM, March 12, 1972. Drilled to 1243'. Ran 38 joints and 1 cut joint, 1230' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 1243' with 300 sacks of Class C with 4% gel and 2% Ca C12 and 100 sacks of Class C with 2% Ca C12. Cement circulated. WOC and NU 18-1/2 hours, Tested casing with 1800#, 30 minutes. OK.

Started drilling 7-7/8" hole at 1243' at 6:00 PM, March 13, 1972.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>C. D. Kallinger</u>	TITLE <u>Area Engineer</u>	DATE <u>March 14, 1972</u>
-------------------------------	----------------------------	----------------------------

APPROVED BY <u>Joe D. Ramsey</u> Dist. I, Supv.	TITLE _____	DATE <u>MAR 15 1972</u>
--	-------------	-------------------------

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR 14 1972

OIL CONSERVATION COMM.  
HOBBS, N. M.