

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION
WELL COMPLETION OR RECOMPLETION REPORT AND LOG

Form O-105
Revised 1-1-65

5a. Indicate Type of Lease
Lease ☒ Other ☐

5. State Oil & Gas Lease No.
B-9131 L-4428

1. TYPE OF WELL
OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐

2. TYPE OF COMPLETION
NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ OTHER ☐

7. Unit Agreement Name

3. Name of Operator
Western Oil Producers, Inc.

8. Farm or Lease Name
State Com.

4. Address of Operator
Box 2055, Roswell, New Mexico 88201

9. Well No.
41

5. Location of Well
M 3300 South 650

10. Field and Pool, or Wildcat
Ossido Morrow ext.

6. Section, Township, Range, N.M.P.M.
West LINE OF SEC. 5 TWP. 21-S RGE. 35-E N.M.P.M.

12. County
Lea

15. Date Spudded
10/18/72

16. Date T.D. Reached
12/7/72

17. Date Compl. (Ready to Prod.)
1/24/73

18. Elevations (DF, RKB, RT, GR, etc.)
G.L. 3644

19. Elev. Casinghead
3644

20. Total Depth
11,550'

21. Plug Back T.D.
11,465'

22. If Multiple Compl., How Many
0

23. Intervals Drilled By
Rotary Tools ☒ Cable Tools ☐

24. Producing Interval(s), of this completion - Top, Bottom, Name
11,319' - 11,458' Morrow

25. Was Directional Survey Made
No

26. Type of Electric and Other Logs Run
Induction & Gamma-Ray Neutron

27. Was Well Cored
No

28. CASING RECORD (Report all strings set in well)

29. LINER RECORD

30. TUBING RECORD

31. Perforation Record (Interval, size and number)
4 1/2" csg. slotted w/3-3" slots/ft.
11,319' - 11,329' & 11,372" - 11,458"

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

33. PRODUCTION

34. First Production
1/24/73

35. Production Method (Flowing, gas lift, pumping - Size and type pump)
Flowing

Well Status (Prod. or Shut-in)
S.I. W.O.P.L.

36. Hours Tested
5

37. Choke Size
22/64

38. Prod'n. For Test Period
TR.

39. Oil - Bbl.
1905.0

40. Gas - MCF
1904.0

41. Water - Bbl.
0

42. Gas - Oil Ratio
TSTM

43. Casing Pressure
0

44. Calculated 24-Hour Rate

45. Oil - Bol.

46. Gas - MCF
1904.0

47. Water - Bbl.
0

48. Oil Gravity - API (Corr.)

49. Composition of Gas (Sold, used for fuel, vented, etc.)
to be sold to Southern Union

50. List of Attachments
Logs & 4 point test

51. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNED *[Signature]* TITLE Supt. DATE 3/15/73

Test Witnessed By
Ken Reynolds

This form is to be filled with the appropriate District Office of the Commission, not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filled in quintuplicate except on state land, where six copies are required. See Rule 1105.

INSTRUCTIONS

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Canyon	10610	T. Ojo Alamo	T. Penn. "B"
T. Strawn	10790	T. Kirtland-Fruitland	T. Penn. "C"
T. Atocha		T. Pictured Cliffs	T. Penn. "D"
T. Miss		T. Cliff House	T. Leadville
T. Devonian		T. Menefee	T. Madison
T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg		T. Mancos	T. McCracken
T. San Andres		T. Gallup	T. Ignacio Qizte
T. Glorieta		T. Base Greenhorn	T. Granite
T. Paddock		T. Dakota	T.
T. Ellensburg		T. Morrison	T.
T. Blinberry		T. Todillo	T.
T. Tubb		T. Granite	T.
T. Drinkard		T. Delaware Sand	T.
T. Abo		T. Bone Springs	T.
T. Wolfcamp	10460	T. First Sand	8570
T. Penn. Morrow	11210	T. 2nd Sand	9460
T. Penn. (Bough C)		T. 3rd Sand	10300
T. Cisco		T. Penn. "A"	T.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1785	1785	Redbed and Red sand				
1785	1890	105	Anhy.				
1890	3480	1590	Salt				
3480	3700	220	Anhy. & Dolo				
3700	5210	1510	Dolo, Gyp, Sand				
5210	8570	3360	Dark lime & Dolo				
8570	8990	420	Dark lime & Sand				
8990	9460	470	Dark lime				
9460	9710	250	Sand				
9710	10300	590	Lime-dark				
10300	10460	160	Sand				
10460	10610	150	Lime & Shale				
10610	10790	180	Lime & Chert				
10790	11210	420	Sand, lime, chert				
11210	11310	100	Shale & Lime				
11310	11540	230	Sand & Shale				