

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

N.M. 026684

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "One"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Hat Mesa

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 1, T-21-S, R-32-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3774 G.L.

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETION

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1. Set cast iron bridge plug in 5-1/2" casing above perforations @ 13,700'.
2. Spotted 25 sx Class "H" cmt on top of CIBP @ 13,700'.
3. Displaced packer fluid in csg w/10 ppg fluid.
4. Placed 25 sx Class "H" cmt plug in 5-1/2" csg @ 13,011-12,774'.
5. Placed 40 sx Class "H" cmt plug across top of 5-1/2" liner into 7-5/8" liner @ 11,255'-10,997'.
6. Placed 25 sx Class "H" cmt plug in 7-5/8" csg @ 8,904-8,781'.
7. Placed 25 sx Class "H" cmt plug in 7-5/8" csg @ 6427-6304'.
8. Placed 56 sx Class "H" cmt plug across top of 7-5/8" liner into 9-5/8" csg @ 3825-3642'.
9. Placed 40 sx Class "H" cmt plug in 9-5/8" csg @ 1725-1611'.
10. Placed 35 sx Class "H" plug in 9-5/8" csg @ 1223-1151'.
11. Placed 60' cmt plug from 60' to surface in top of 9-5/8" csg.
12. Welded plate on csg & installed marker on top of plate.
13. Well P&A 8-13-85.

18. I hereby certify that the foregoing is true and correct

SIGNED

James E. Pryor
James E. Pryor

(This space for Federal or State office use)

APPROVED BY

Don X. Man

CONDITIONS OF APPROVAL, IF ANY:

TITLE

District Superintendent

DATE

8/14/85

TITLE

DATE

4-7-87

*See Instructions on Reverse Side