

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE  
(Other Instructions  
reverse side)

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 093840

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Pubco Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T. R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 2, T-21-S, R-32-E

12. COUNTY OR PARISH 13. STATE

Lea N. Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Amini Oil Company

3. ADDRESS OF OPERATOR

405 Wall Towers East - Midland, Tx. 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

3300' FNL & 660' FWL

14. PERMIT NO.

Letter of 3-27-73

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3719' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Drilling Progress

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-5-73 Drilled 8 1/2" hole to T.D. of 14407'. Ran 20# & 17# 8rd lt&c 5 1/2" liner & hung @10968'. Bottom set @14407'. Cemented w/425 sx Halliburton light weight (10# salt & 3/4 of 1% CFR-2 per sk.) + w/300 sx class H neet (3# KCL & 1 1/2% CFR-2 per sk.). Plugged down @7:15 PM.

6-6-73 W.O.C. 24 hrs. Tested w/2000# psi for 30 mins. - Held OK.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Farin Rodwin*

TITLE Agent

DATE 6-15-73

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 18 1973

\*See Instructions on Reverse Side

U.S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO