## ID STATES UN DEPARTMENT OF THE INTERIOR (Other Instructions verse side)

SUBMIT IN TRIPL

LE.

Form approved. Budget Bureau No. 42-R1424. 5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY NM-13741

CHAIDDA	NIOTICES	AND	DEDODIC	ONL	WELLC
SUNDRY	NOHICES	ANU	REPORTS	UN.	MELLS

	SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	OIL X GAS OTHER	7. UNIT AGREEMENT NAME
	John H. Hendrix	8. FABM OR LEASE NAME Jones-Federal
3. 4	ADDRESS OF CPERATOR	9. WELL NO.
	403 Wall Towers West, Midland, Texas 79701	1
9	LOCATION OF WELL (Report Recation clearly and in a cordance with any State requirements.*  See also space 17 below.)  At surface	D-K Drinkard
	Unit Letter L, 990' FWL & 2310' FSL Sec. 30, T-20-S, R-39-E.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T-20-S,
		R-39-E
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR. etc.)	12. COUNTY OR PARISH 13. STATE
	3558,9' GL	Lea New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF IN	TENTION TO:	SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	FULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL,	
FRACTURE TREAT	MULTIPLE COMP ETE	FRACTURE TREATMENT	ALTERING CASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*	
REPAIR WELL	CHANGE PLANS	(Other) <u>Casing set</u>		
(Other)		(Note: Report results of mult Completion or Recompletion Re	tiple completion on Well sport and Log form.)	

- 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.).
  - 1. Leatherwood Drilling Company spudded @ 11:45 a.m. (MST) 11-13-74.
  - Drilled 11" hole to 1652'.
  - Ran 44 jts. (1667') 24# J-55, 8 5/8" casing set @ 1652'. 3.
  - Cemented w/350 sxs. Class H, 4% gel, 2% CaCl and 300 sxs. Class H, 2% gel, 2% CaCl. Plug down @ 12:45 a.m. (MST) 11-16-74. Cement circulated.
  - 5. WOC for 18 hours. Tested pressure casing to 900%. Tested ok.

8. I hereby certify that the foregoing is true/and correct	
SIGNED SULLENGE TO THE TITLE	Production Clerk DATE 11-18-74
(This space for Federal or State office use)	FOR HEAD
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	THEY CHRYEY
*See Instri	uctions on Reverse Sides, NEW MEXICO