DISTRIBUTION SANTA FE	NEW MEXICO OIL CONSE	ERVATION COMMISSION	Form C-103 Supersedes Old C-102 and C-103 Effective 1-1-65
FILE			
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE			State XX Fee
OPERATOR			5. State Oil & Gas Lease No.
			E 2523
SUNI	DRY NOTICES AND REPORTS ON	WELLS	
(DO NOT USE THIS FORM FOR USE "APPLIC	DRY NOTICES AND REPORTS ON PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BA ATION FOR PERMIT -" (FORM C-101) FOR SUCH	CK TO A DIFFERENT RESERVOIR.	
1.			7. Unit Agreement Name
OIL XX GAS WELL OTHER-			N A
2. Name of Operator			8. Farm or Lease Name
Jack M	arkham		State 36
3. Address of Operator			9. Well No.
Suite 1212 - 1500	Broadway - Lubbock, Texas	79401	1
4. Location of Well			10. Field and Pool, or Wildcat
I I	1980 FEET FROM THE SOUTH	LINE AND 660	Drinkard
ONII CEITER	TEET FROM THE	THE AND	
- East	TION 36 TOWNSHIP 21-	-S 36-E	
THE LINE, SEC	TIONTOWNSHIP	RANGENMPM	
	15. Elevation (Show whether I	DF, RT, GR, etc.)	12. County
	3482 GR; 3494 KB	(datum)	Lea
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
other	Operations (Clearly state all pertinent deta	COMMENCE DRILLING OPNS. CASING XXXXXX C CEMENT JOB X OTHER ils, and give pertinent dates, including	PLUG AND ABANDONMENT
other 17. Describe Proposed or Completed work) SEE RULE 1103. TD 6831' Ran 173 jt 6826 feet with: 250 sentonite, 8# salt at Ran 1000 gal. mud flinkrs WOC temperature,	CHANGE PLANS Operations (Clearly state all pertinent deta	commence Drilling OPNS. CASING XXXXXX D CEMENT JQB X other ils, and give pertinent dates, including 7#, LT&C, 8 Rd Thd. new Flocele/sk.; and 700 s lated slurry volume 25 down 4:00 PM MDT, Sept ase salt 2495 ft.). Re	casing. Cemented at Class "C" Pozmix w/2% 1.5 bbl. (1412 ft.) 8, 1975. After 12
other 17. Describe Proposed or Completed work) SEE RULE 1103. TD 6831' Ran 173 jt 6826 feet with: 250 sentonite, 8# salt at Ran 1000 gal. mud flinkrs WOC temperature,	Operations (Clearly state all pertinent deta s. (6815' net) 5-½" 0 D, 1 Ex Halliburton Lite w½ 1b. and ½ 1b. Flocele/sk. (calculate shead of cement. Plug top cement & 2500 feet (Ba	commence Drilling OPNS. CASING XXXXXX D CEMENT JQB X other ils, and give pertinent dates, including 7#, LT&C, 8 Rd Thd. new Flocele/sk.; and 700 s lated slurry volume 25 down 4:00 PM MDT, Sept ase salt 2495 ft.). Re	casing. Cemented at Class "C" Pozmix w/2% 1.5 bbl. (1412 ft.) 8, 1975. After 12
other 17. Describe Proposed or Completed work) SEE RULE 1103. TD 6831' Ran 173 jt 6826 feet with: 250 sentonite, 8# salt at Ran 1000 gal. mud flinkrs WOC temperature,	Operations (Clearly state all pertinent deta s. (6815' net) 5-½" 0 D, 1 Ex Halliburton Lite w½ 1b. and ½ 1b. Flocele/sk. (calculate shead of cement. Plug top cement & 2500 feet (Ba	commence Drilling OPNS. CASING XXXXXX D CEMENT JQB X other ils, and give pertinent dates, including 7#, LT&C, 8 Rd Thd. new Flocele/sk.; and 700 s lated slurry volume 25 down 4:00 PM MDT, Sept ase salt 2495 ft.). Re	casing. Cemented at Class "C" Pozmix w/2% 1.5 bbl. (1412 ft.)
other 17. Describe Proposed or Completed work) SEE RULE 1103. TD 6831' Ran 173 jt 6826 feet with: 250 sentonite, 8# salt at Ran 1000 gal. mud flinkrs WOC temperature,	Operations (Clearly state all pertinent deta s. (6815' net) 5-½" 0 D, 1 Ex Halliburton Lite w½ 1b. and ½ 1b. Flocele/sk. (calculate shead of cement. Plug top cement & 2500 feet (Ba	commence Drilling OPNS. CASING XXXXXX D CEMENT JQB X other ils, and give pertinent dates, including 7#, LT&C, 8 Rd Thd. new Flocele/sk.; and 700 s lated slurry volume 25 down 4:00 PM MDT, Sept ase salt 2495 ft.). Re	casing. Cemented at Class "C" Pozmix w/2% 1.5 bbl. (1412 ft.)
other 17. Describe Proposed or Completed work) SEE RULE 1103. TD 6831' Ran 173 jt 6826 feet with: 250 sentonite, 8# salt at Ran 1000 gal. mud flinkrs WOC temperature,	Operations (Clearly state all pertinent deta s. (6815' net) 5-½" 0 D, 1 Ex Halliburton Lite w½ 1b. and ½ 1b. Flocele/sk. (calculate shead of cement. Plug top cement & 2500 feet (Ba	commence Drilling OPNS. CASING XXXXXX D CEMENT JQB X other ils, and give pertinent dates, including 7#, LT&C, 8 Rd Thd. new Flocele/sk.; and 700 s lated slurry volume 25 down 4:00 PM MDT, Sept ase salt 2495 ft.). Re	casing. Cemented at Class "C" Pozmix w/2% 1.5 bbl. (1412 ft.)

المسلمطين وأسب

TITLE __

DATE __

APPROVED BY_